

# **SAFETY DATA SHEET**

Creation Date 27-Apr-2009 Revision Date 18-Jan-2018 Revision Number 6

1. Identification

Product Name Methanol

Cat No.: A434-20; A450-4; A455-1; A457-4; LCMSKIT; OPTIMAKIT; SC95-1;

SW2-1; TIA947-4; TIA947P-200L; HC4001GAL; 22-050-135; 22-110-675;

22-110-887

**CAS-No** 67-56-1

Synonyms Methyl alcohol;

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

### **Emergency Telephone Number**

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 2
Acute oral toxicity
Category 3
Acute dermal toxicity
Category 3
Acute Inhalation Toxicity - Vapors
Specific target organ toxicity (single exposure)
Category 1
Target Organs - Optic nerve.
Specific target organ toxicity - (repeated exposure)
Category 1

Target Organs - Kidney, Liver, spleen, Blood.

Label Elements

## Signal Word

Danger

### **Hazard Statements**

Highly flammable liquid and vapor Toxic if swallowed Toxic in contact with skin Toxic if inhaled

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

## Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

#### Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

## Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposa

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous.

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl alcohol	67-56-1	>95

## 4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if

victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate

medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms and

effects

Notes to Physician

Breathing difficulties. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

Unsuitable Extinguishing Media Water may be ineffective

**Flash Point** 12 °C / 53.6 °F

**Method -** No information available

Autoignition Temperature 455 °C / 851 °F

**Explosion Limits** 

**Upper** 31.00 vol % **Lower** 6.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

## Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

### **Hazardous Combustion Products**

Carbon monoxide (CO) Formaldehyde

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards130N/A

## 6. Accidental release measures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use

personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Take precautionary measures against static discharges.

**Environmental Precautions** Should not be released into the environment. See Section 12 for additional ecological

information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Revision Date 18-Jan-2018 Methanol

Up

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

Handling

Wear personal protective equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment

must be grounded. Take precautionary measures against static discharges.

**Storage** 

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

## 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	TWA: 260 mg/m <sup>3</sup>
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	STEL: 250 ppm
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	STEL: 310 mg/m <sup>3</sup>
		Skin	STEL: 325 mg/m <sup>3</sup>	_
		TWA: 200 ppm	_	
		TWA: 260 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area **Hygiene Measures** 

and clothing.

## Physical and chemical properties

Liquid **Physical State** Colorless **Appearance** Alcohol-like Odor

**Odor Threshold** No information available

Not applicable рΗ -98 °C / -144.4 °F Melting Point/Range

64.7 °C / 148.5 °F @ 760 mmHg **Boiling Point/Range** 

12 °C / 53.6 °F **Flash Point** 

**Evaporation Rate** 5.2 (ether = 1) **Flammability (solid,gas)** Not applicable

Flammability or explosive limits

 Upper
 31.00 vol %

 Lower
 6.0 vol %

Vapor Pressure 128 hPa @ 20 °C

Vapor Density1.11Specific Gravity0.791

Solubility
Miscible with water
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Miscible with water
No data available
455 °C / 851 °F
No information available

 $\begin{array}{ccc} \textbf{Viscosity} & 0.55 & \text{cP at } 20 \ ^{\circ}\text{C} \\ \textbf{Molecular Formula} & \text{C H4 O} \end{array}$ 

Molecular Weight 32.04 VOC Content(%) 100

Surface tension 0.02255 N/m @ 20°C

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases,

Metals, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	Calc. ATE 60 mg/kg	Calc. ATE 60 mg/kg	Calc. ATE 0.6 mg/L (vapours) or
•	LD50 > 1187 – 2769 mg/kg ( Rat )	LD50 = 17100 mg/kg ( Rabbit )	0.5 mg/L (mists)
			LC50 = 128.2 mg/L ( Rat ) 4 h

**Toxicologically Synergistic** 

Carbon tetrachloride

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** May cause skin and eye irritation

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl alcohol	67-56-1	Not listed				

Mutagenic Effects No information available

**Reproductive Effects** No information available.

Revision Date 18-Jan-2018 Methanol

**Developmental Effects** Component substance is listed on California Proposition 65 as a developmental hazard.

**Teratogenicity** No information available.

STOT - single exposure Optic nerve

Kidney Liver spleen Blood STOT - repeated exposure

No information available **Aspiration hazard** 

delayed

Symptoms / effects,both acute and May cause blindness: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

### **Ecotoxicity**

	Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
I	Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
	-		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
				EC50 = 43000 mg/L 5 min	

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl alcohol	-0.74

## 13. Disposal considerations

Waste Disposal Methods Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

## 14. Transport information

DOT

UN1230 **UN-No Proper Shipping Name METHANOL** 

**Hazard Class** 3 **Packing Group** Ш

**TDG** 

UN-No UN1230 **Proper Shipping Name METHANOL** 

**Hazard Class Subsidiary Hazard Class** 6.1 **Packing Group** Ш

**IATA** 

**UN-No** UN1230 **Proper Shipping Name METHANOL** 

**Hazard Class** 3 **Subsidiary Hazard Class** 6.1 **Packing Group** 

IMDG/IMO

UN-No UN1230
Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

## Regulatory information

#### **International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Methyl alcohol	Х	Χ	-	200-659-6	-		Χ	Χ	Χ	Χ	Х

### Legend:

X - Listed

- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %	
Methyl alcohol	67-56-1	>95	1.0	

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

**OSHA** Occupational Safety and Health Administration

Not applicable

**CERCLA** 

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs		
Methyl alcohol	5000 lb	-		

California Proposition 65 This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental

## U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X

#### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 27-Apr-2009

 Revision Date
 18-Jan-2018

 Print Date
 18-Jan-2018

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**