
 SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID : M3000-1
 PRODUCT CLASS : PAINT, WATER BASE
 TRADE NAME : C.G. ONE COAT ACRYLIC HOUSE PAINT
 FORMULA ID : 10-1
 MSDS PREPARATION DATE : 06/28/2004
 MANUFACTURER IDENTIFICATION:
 NAME : CORONADO PAINT CO.
 ADDRESS : 308 OLD COUNTY ROAD

TELEPHONE : 386-428-6461
 EMERGENCY CONTACT : CHEMTREC
 EMERGENCY TELEPHONE : (800) 424-9300
 EDGEWATER FL 32132

 SECTION 2 - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

1

CAS# 107-21-1
 ETHYLENE GLYCOL
 PCT BY WT: 3.3630 VAPOR PRESSURE: .060 MMHG @ 68F
 EXPOSURE LIMIT:
 ACGIH CEILING: 100 mg/cu m (As an aerosol)
 OSHA CEILING: 50 ppm
 LD50: Oral (Rat)- 4.0 g/kg
 CA PROPOSITION 65: Yes

2

CAS# 13463-67-7
 TITANIUM DIOXIDE
 PCT BY WT: 15 - 20
 EXPOSURE LIMIT:
 ACGIH TLV/TWA: 10 mg/cu m (Total Dust) - TWA
 OSHA PEL/TWA: 10 mg/cu m (Total Dust) - TWA
 LD50: Oral (Rat)- >7500 mg/kg (Ti02)

3

CAS# 1314-13-2
 ZINC OXIDE
 PCT BY WT: 2.2680
 EXPOSURE LIMIT:
 ACGIH TLV/TWA: Fume: TWA 5 mg/cu m
 ACGIH TLV/STEL: STEL 10 mg/cu m
 OSHA PEL/TWA: Fume: TWA 5 mg/cu m; TWA Total Dust: 10 mg/cu m
 OSHA STEL: Fume: 10 mg/cu m
 LC50: Inhalation, Mouse - 2500 mg/cu m
 LD50: Oral, Mouse - 7950 mg/kg

4

CAS# 14808-60-7
 CRYSTALLINE SILICA - QUARTZ
 PCT BY WT: 1.3650
 EXPOSURE LIMIT:
 ACGIH TLV/TWA: TWA 0.10 mg/cu m (Respirable Dust)

 CORONADO PAINT CO.
 MATERIAL SAFETY DATA SHEET

M3000-1

 OSHA PEL/TWA: TWA 0.10 mg/cu m (Respirable Fraction)
 CA PROPOSITION 65: Yes

 This product contains one or more reported carcinogens or suspected carcinogens which are noted in Section 3, Hazards Identification, CARCINOGENICITY.

 This product contains one or more Hazardous Air Pollutants.

 This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

 This product contains one or more reported or suspected reproductive toxins.

 SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Primary irritant.

SKIN: N/A

INHALATION: With poor ventilation, vapor or spray mist may irritate respiratory mucous membranes, causing headache & nausea.

INGESTION: N/A

CHRONIC EFFECTS:

Ethylene glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans. Prolonged overexposure to ethylene glycol may cause adverse effects to the reproductive system.

ROUTE(S) OF EXPOSURE

Exposure may be inhalation and/or skin or eye contact, depending on conditions of use.

CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

 SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

CORONADO PAINT CO.
MATERIAL SAFETY DATA SHEET

M3000-1

-
- SKIN CONTACT:** Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.
- INHALATION:** If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.
- INGESTION:** If victim is conscious, give 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center at once.
- NOTE TO PHYSICIAN:**
Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : N/A
Flashpoint : N/A
Explosion Level : Low - .6
High - 15.3

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. After water evaporates, remaining material will burn; use CO₂, dry chemical or foam (National Fire Protection Association Class B extinguisher).

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat; use water spray to cool. Product in open containers may spatter when the temperature exceeds boiling point of water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate as described in Section 5. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely. Avoid discharge into drains, sewers or waterways.

CLEAN-UP

Collect by absorption, shovel and/or wet mopping.

 CORONADO PAINT CO.
 MATERIAL SAFETY DATA SHEET

M3000-1

 SECTION 7 - HANDLING AND STORAGE

HANDLING

Transfer only to approved containers with complete & appropriate labeling. Do not take internally. Keep out of the reach of children.

STORAGE

Do not store above 120 Degrees F. Close container after each use.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet. Avoid FREEZING this product.

 SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to chemicals in Section 2 is maintained below applicable exposure limits.

RESPIRATORY PROTECTION

Where exposures are below the PEL, no respiratory protection is required. Where exposures exceed the PEL, use a respirator approved by NIOSH or a full protective suit with air supply appropriate for the chemical(s) and level of exposure.

EYE PROTECTION

Wear safety spectacles with unperforated side shields.

PROTECTIVE GLOVES

None required for normal application of limited duration is expected. For long or repeated contact, wear chemical resistant gloves.

 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Density	:	N/A
Vapor Pressure	:	17mmHg@ 68 Degrees F (water)
Physical State	:	LIQUID
Boiling Point Range	:	Lower - 212.0 °F Higher - 401.0 °F
Specific Gravity	:	1.321
Weight per Volume	:	10.9968 LB/GL
VOC - Total (lbs./gal)	:	1.218
Evaporation Rate	:	.010 (n-Butyl Acetate = 1)
Volatile by Weight	:	49.4194
Volatile by Volume	:	64.8482

CORONADO PAINT CO.
MATERIAL SAFETY DATA SHEET

M3000-1

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

None known.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS PRODUCTS OF DECOMPOSITION

Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS	: N/A
DOT PACKAGING GROUP	: N/A
DOT LABEL	: NONE
DOT SHIPPING NAME	: PAINT
DOT PLACARD	: NONE
UN/NA NUMBER	: NONE

CORONADO PAINT CO.
MATERIAL SAFETY DATA SHEET

M3000-1

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLENE GLYCOL

CAS# 107-21-1 PCT BY WT: 3.3630

ZINC OXIDE

CAS# 1314-13-2 PCT BY WT: 2.2680

SECTION 16 - OTHER INFORMATION

Prepared by : Ronnie Darley
Date of issue : 06/28/2004
Last Revision Date : 08/28/2002

MSDS Prepared for :

MSDS Last Prepared : NONE
HMIS Rating: Health- 1 Flammability- 0
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety

From:

06/28/2004 13:50 #013 P.014/014

CORONADO PAINT CO.
MATERIAL SAFETY DATA SHEET

M3000-1

Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL - Short Term Exposure Limit; N/A - Not applicable; IARC - International Agency for Research on Cancer; NE - Not established; NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - 29 CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.