REVISION DATE:

# MATERIAL SAFETY DATA SHEET CT 4-A

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME

CT 4-A

PRODUCT USE

Oil Based Rust Preventive Additive

SUPPLIER

Chemtool Incorporated 8200 Ridgefield Road

P.O. Box 538

Crystal Lake, IL 60039-0538

Tel: (815) 459-1250 Fax: (815) 459-1955

**EMERGENCY TELEPHONE** 

Infotrac

U.S. and Canada - (800) 535-5053

Outside the U.S. and Canada - 001-352-323-3500

# 2. COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT NAME

CAS No.

WEIGHT

DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED LIGHT NAPHTHENIC DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC

64742-53-6 64742-52-5 30-50 %

COMPOSITION COMMENTS

Refer to section eight for exposure limits on ingredients.

Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

## 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

#### **ACUTE EFFECTS**

HEALTH HAZARDS, GENERAL

Prolonged exposure to product mist or vapors may cause respiratory irritation.

#### CHRONIC EFFECTS

SENSITIZATION

No known information.

CARCINOGENICITY

IARC: Not listed. NTP: Not listed. OSHA: Not regulated.

TERATOGENICITY

No known information.

#### HEALTH WARNINGS

INHALATION, Oil mist can irritate airways and lungs. Single exposure to vapors is not likely to be hazardous. SKIN CONTACT. Slightly irritating. Repeated or prolonged

contact can result in drying of the skin. EYE CONTACT, Irritating, INGESTION, Car cause discomfort. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

#### OTHER INFORMATION

ROUTE OF ENTRY

EYES

Skin and/or eye contact, Ingestion, Inhalation,

## 4. FIRST AID MEASURES

INHALATION Remove victim immediately from source of exposure. Get medical attention if any discomfort continues. For breathing difficulties oxygen may be necessary. If breat

stops, provide artificial respiration.

Important! Immediately rinse with water for at least 15 minutes. Get medical atten

if any discomfort continues.

SKIN Immediately remove contaminated clothing. Wash skin thoroughly with soap and

water. Get medical attention if irritation persists after washing.

INGESTION DO NOT induce vomiting. Get medical attention immediately.

# 5. FIRE FIGHTING MEASURES

FLASH POINT (°C) 132 Cd OC (Cleveland open cup).

FLAMMABILITY LIMIT - LOWER(%) 0.9

FLAMMABILITY LIMIT - UPPER(%) 7.0

EXTINGUISHING MEDIA Use: Dry chemicals, sand, dolomite etc. Foam. Carbon dioxide (CO2).

spray may be used to flush spills away from exposures. Caution should be exerc when using water or foam as frothing may occur.

UNUSUAL FIRE & EXPLOSION HAZARDSPressure will increase in over heated, closed containers.

HAZARDOUS COMBUSTION PRODUCTSAcrid smoke/fumes. Oxides of: Carbon, Sulfur.

PROTECTIVE MEASURES IN CASE OF FIREIf-contained breathing equipment and chemical resistant clothing recommend

SPECIAL FIRE FIGHTING PROCEDURES Use water spray to keep fire exposed containers cool and disperse vapors. Water

# 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Minimize skin contact.

PERSONAL PRECAUTIONS Minimize skin contact.

ENVIRONMENT authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

SPILL CLEAN-UP PROCEDURES Contain spill. Neutralize and absorb small amounts. Collect and return large amounts to shipping container. Rinse spill area with water.

Keep product out of sewers and watercourses by diking or impounding. Advise

PRECAUTIONS TO PROTECT THE

## 7. HANDLING AND STORAGE

HANDLING PRECAUTIONS Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Do

not reuse container. Keep lid closed when not in use. Do not store or mix with strong

oxidizers.

STORAGE PRECAUTIONS Keep away from heat, sparks and open flame. Store separate from strong acids and

oxidizers.

STORAGE CRITERIA Chemical storage.

## EXPOSURE CONTROLS, PERSONAL PROTECTION

COMPONENT STD TWA STEL TWA STEL

5 mg/m3

OSHA

DISTILLATES, PETROLEUM, SEVERELY
HYDROTREATED LIGHT NAPHTHENIC

HYDROTREATED LIGHT NAPHTHENIC

DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC ACGIH 5 mg/m3 OSHA 5 mg/m3

ACGIH 5 mg/m3

10 mg/m3

N/E

N/E

10 mg/m3

#### PROTECTIVE EQUIPMENT





ENGINEERING CONTROLS

Use engineering controls to reduce air contamination to permissible exposure level.

VENTILATION No specific ventilation requirements noted, but forced ventilation may still be required

if air contamination exceeds acceptable level.

RESPIRATORS No specific recommendation made, but respiratory protection may still be required

under exceptional circumstances when excessive air contamination exists.

PROTECTIVE GLOVES For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION Wear splash-proof eye goggles to prevent any possibility of eye contact.

PROTECTIVE CLOTHING Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENIC WORK PRACTICES Wash at the end of each work shift and before eating, smoking and using the toilet.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE

Clear, Liquid.

3/5

Pressure

Temperature (°C)

Temperature (°C)

Reference

Dark, Brown. COLOR Mild (or faint), Citrus ODOR

Insoluble in water.

BOILING POINT (°C, range) >177

-4 MELT/FREEZ, POINT (°C, interval)

SOLUBILITY DESCRIPTION

0.89 DENSITY

VAPOR DENSITY (air=1) >5

VAPOR PRESSURE < 0.5 mmHg

< 0.01 **EVAPORATION RATE** N/A pH-VALUE, CONC. SOLUTION

STABILITY AND REACTIVITY 10.

Normally stable. STABILITY Will not occur. HAZARDOUS POLYMERIZATION

Not applicable POLYMERIZATION DESCRIPTION

HAZARDOUS DECOMPOSITION PRODUCTS des of: Carbon, Sulfur.

11. TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation as such is available. TOXICOLOGICAL INFORMATION

**ECOLOGICAL INFORMATION** 12.

There is no ecological data on the product itself. ECOLOGICAL INFORMATION

DISPOSAL CONSIDERATIONS 13.

Spilled material, unused contents and empty containers must be disposed of in DISPOSAL METHODS accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT HAZARD CLASS Not regulated.

Not regulated. SEA TRANSPORT NOTES

4/5

760mmHg

16

20

BuAc=1

AIR TRANSPORT NOTES

Not regulated.

## 15. REGULATORY INFORMATION

### US FEDERAL REGULATIONS

**SARA 313** SARA 302 CERCLA COMPONENT

DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED LIGHT NAPHTHENIC N/A N/A DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC

N/A N/A N/A N/A

#### CLEAN AIR ACT

SARA(311/312) HAZARD CATEGORIES None

#### US STATE REGULATIONS

#### WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHIMIS

	INVENTORIES							
COMPONENT	CAN	บร	EU	AUS	JAP	KOR	CHN	PHLE
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED LIGHT NAPHTHENIC	DSL	Yes	NAV	NAV	NAV	NAV	NAV	NAV
DISTILLATES, PETROLEUM, SEVERELY HYDROTREATED HEAVY NAPHTHENIC	DSL	Yes	EINECS	Yes	No	Yes	NAV	Yes

## 16. OTHER INFORMATION

HEALTH Irritation, minor residual injury (1)

Burns only if pre-heated (1). FLAMMABILITY

REACTIVITY N/A (0).

PREPARED BY John Dingess

DATE November 26, 2003

DISCLAIMER While the information and recommendations set forth herein are believed to be

accurate as of the date thereof. Chemtool Incorporated makes no warranty with

respect thereto and disclaims all liability from reliance therein.