MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035 PH: 1-800-321-3444 FAX: 330-650-1453

FLOETROL

SECTION I - PRODUCT IDENTIFICATION						
NAME OF MANUFAC	TURER	The F	lood Company			
			1212 Barlow Road			
			P.O. Box 2535			
			Hudson, Ohio 44236-0035 U.S.A.			
EMERGENCY TELEPHONE NO.			800-321-3444 or your local			
			poison control center			
TRANSPORTATION			Chemtrec 800-424-9300 (24 hours)			
PRODUCT NAME			FLOETROL			
PRODUCT CLASS			Water reducible additive for latex coatings			
			DATE OF PREPARATION/CHANGE			
The second secon			9/1/99			
PREPARED BY	PREPARED BY Safety & Compliance Officer					
SECTION II - HAZARDOUS INGREDIENTS						
INGREDIENT	PERCENT	OCCUPATIONAL	VAPOR	LD50	LC50	
		EXPOSURE LIMIT	PRESSURE			
		TLV PEL				
Not hazardous	N/A	N/A□	N/A□	N/A	N/A□	
under Department	N/A	N/A□	N/A□	N/A□	N/A□	
	N/A	N/A□	N/A□	N/A□	N/A□	
under Department	N/A	N/A□	N/A□	N/A□	N/A□	
under Department		N/A SECTION III - PHYS		N/A□	N/A□	
under Department		SECTION III - PHYS		N/A□	N/A□	
under Department of Labor definitions.		SECTION III - PHYS	ICAL DATA	N/A□	N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RAT		SECTION III - PHYS	ICAL DATA 12 DEGREES F.		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY		SECTION III - PHYS 2 N S	ICAL DATA 12 DEGREES F. /A		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RAT		SECTION III - PHYS 2 N S	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER		N/AD	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME	E	SECTION III - PHYS 2 N S 9 8	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATI VOLATILE VOLUME WEIGHT/GALLON	E	SECTION III - PHYS 2 N S 9 8	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A	E SECTION I	SECTION III - PHYS 2 N S 9 8 N V - FIRE AND EXPLO	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI	E SECTION I	SECTION III - PHYS 2 N S 9 8 N V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA		N/A□	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATI VOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI (X) DRY CHEMICAL	SECTION I	SECTION III - PHYS 2 N S 9 8 V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL WATER FOG	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA		N/AD	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI (X) DRY CHEMICAL UNUSUAL FIRE AND	SECTION I	SECTION III - PHYS 2 N S 9 8 N V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL WATER FOG N HAZARDS: None	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA		N/AD	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI (X) DRY CHEMICAL UNUSUAL FIRE AND NOTE: Non-Flamma	EDIA: () FO	SECTION III - PHYS 2 N S 9 8 N V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL WATER FOG N HAZARDS: None	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA		N/AD	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI (X) DRY CHEMICAL UNUSUAL FIRE AND NOTE: Non-Flamma EXPLOSION HAZAR	EDIA: () FO () EXPLOSION able in liquion DS: None	SECTION III - PHYS 2 N S 9 8 V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL WATER FOG N HAZARDS: None	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA FOAM () CO2		N/AD	
under Department of Labor definitions. BOILING RANGE VAPOR DENSITY EVAPORATION RATIVOLATILE VOLUME WEIGHT/GALLON pH FLASH POINT: N/A EXTINGUISHING MI (X) DRY CHEMICAL UNUSUAL FIRE AND NOTE: Non-Flamma	EDIA: () FO () EXPLOSION able in liquion DS: None	SECTION III - PHYS 2 N S 9 8 V - FIRE AND EXPLO LEL: - N/A DAM () ALCOHOL WATER FOG N HAZARDS: None	ICAL DATA 12 DEGREES F. /A LOWER THAN ETHER 0% .37 LBS/GAL /A DSION HAZARD DATA FOAM () CO2		N/AD	

MSDS 9/1/99 Page 1

MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035 PH: 1-800-321-3444 FAX: 330-650-1453

FLOETROL

SECTION V - TRANSPORTATION DATA

DOT - Not Regulated in any size.

SECTION VI - TOXICOLOGICAL PROPERTIES

EFFECTS OF OVEREXPOSURE:

SKIN: Prolonged or repeated contact with skin may cause some skin irritation depending on the individual's sensitivity but no serious dermatitis hazard is anticipated.

EYE: May cause mild eye irritation.

INHALATION: No significant signs indicative of adverse health effects are expected with the use of this product.

SWALLOWING: No significant signs indicative of adverse health effects are expected with the use of this product.

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Avoid excessive skin contact.

PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL () INHALATION (X) INGESTION (X) EYE

SECTION VII - FIRST AID PROCEDURES

SKIN: Wash affected area with soap and water

EYE: Flush immediately with large amounts of water for at least 15 minutes. If irritation persists, get medical attention.

INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist.

SWALLOWING: If large amounts are swallowed or if irritation occurs, seek medical attention.

Drink one or two glasses of water. Do not induce vomiting or give anything by mouth to an unconscious person.

SECTION VIII - REACTIVITY DATA

STABILITY: () UNSTABLE (X) STABLE

HAZARDOUS POLYMERIZATION: () MAY OCCUR (X) WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: None

CONDITIONS TO AVOID: Heat

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and bases (caustic).

SECTION IX- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Very small quantities can be wiped or swept up.

MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035 PH: 1-800-321-3444 FAX: 330-650-1453

FLOETROL

WASTE DISPOSAL METHOD: Dispose in accordance with all local, State, and Federal regulations.

SECTION X - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: Not needed with normal use.

VENTILATION: Normal room ventilation but if conditions cause vapors to accumulate, provide

a mechanical exhaust.

PROTECTIVE GLOVES: Usually not needed, however, if prolonged contact is probable, use

rubber or plastic gloves.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: None needed.

HYGIENIC PRACTICES: Wash hands with soap and water thoroughly after use.

SECTION XI - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid excessive heat an cold.

OTHER PRECAUTIONS: None

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS#

Chemical Name

% by Weight

NONE

NONE

NONE

This information is furnished without warranty, except it is accurate to the best of The Flood Company's knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which The Flood Company assumes legal responsibility expressed or implied.

Last update 9/1/99, Section I, VI, VII, X, XI