

Part Number: CL-021

Last Revised: September 9, 2013

Section 1 - Material Identification

Supplier: Martin Engineering

One Martin Place Neponset, IL 61345

Telephone: 1-800-544-2947

CHEMTREC (24 HR Emergency Telephone), call: 1-800-424-9300

Medical: Rocky Mountain Poison Center: 1-303-623-5716

Trade Name: Dust Control Agent

Product Description: An opaque to white liquid having a slightly acrylic odor.

Product Use: Used as a dust control agent in industrial applications.

Section 2- Hazardous Ingredients

Classification: A white liquid having a slight characteristic odor. The mists and liquid may cause irritation to the eyes and skin. Inhalation of mists may cause mild or moderate irritation to the entire respiratory tract

Primary Routes of exposure: Skin contact and inhalation.

Slip Hazard: Slip hazard when spilled.

Eyes: Exposure to the mists or liquid may cause eye irritation. Symptoms of exposure may include

tearing, redness and irritation.

Skin: No more than slightly toxic. (based on components)

Ingestion: No more than slightly toxic. (based on components)

Remarks: Handle in accordance with good industrial hygiene and safety practices.

CAS#	Chemical	Composition
Proprietary*	Vinyl-acrylic based polymer	2%
7732-18-5	Water	96%
137-40-6	Sodium Propionate	0-1%
9005-65-6	Tween 80	0-1%

^{*}The specific chemical identity is withheld because it is trade secret information to the supplier.

While this material is not classified as hazardous under Federal OSHA regulations, this MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other uses of this product.

Section 3 - Physical Data

Freezing Point: Less than 0°C Boiling Point: Greater than 100°C

Physical State: Liquid
Solubility in Water: Miscible
Appearance: White

Odor: Slighty acrylic
pH: estimated 4.5-5.5
Specific Gravity: 0.9982 g/ml at 20°C
Vapor Pressure: 17.500 mmHg at 20°C
Vapor Density: No Data Available

Section 4 – Fire-Fighting Measures

Suitable Extinguishing Media: Water. Dry Chemical, foam, Carbon dioxide. Use a water spray to

cool the containers exposed to the heat of a fire.

Hazardous Combustion Products: When burned the following hazardous products of combustion

can occur: carbon oxides and hazardous organic compounds.

Specific Hazards: Do not breathe smoke, gases or vapors generated.

Special Protective Equipment

for Firefighters:

In the event of a fire, wear self-contained breathing apparatus

and full protective equipment.

Flashpoint and Method Limits: NA
Flammable Limits: NA
Auto ignition Temperature: NA

Section 5 – First Aid Measures

General Advice: Remove material from eyes, skin and clothing. In case of doubt

or when symptoms persist, seek medical attention. Wash heavily

contaminated clothing before reuse.

Eye Contact: Hold eyelids apart and flush eyes with a steady, gentle stream of

water for fifteen minutes. If eye irritation persists, seek medical

attention.

Skin Contact: Wash off with soap and plenty of water.

Inhalation: Move to fresh air. If symptoms persist, call a physician. If not

breathing, give artificial respiration.

Ingestion: If swallowed, give plenty of water to drink. Call a physician.

DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person.

Section 6 - Stability and Reactivity Data

Stability: Material is stable under normal and anticipated storage, handling

and processing conditions. Hazardous polymerization does not

occur.

Materials to Avoid: Multivalent metal salts and strong acids.

Conditions to Avoid: Avoid excessive heat and all sources of ignition.

Hazardous Decomposition Products: Thermal decomposition giving flammable and toxic products including

acrylates, carbon oxides, and hazardous organic compounds.

Section 7 - Spill, Leak or Accident Procedures

Land Spill: Wearing recommended protective equipment and clothing dike the spill and pick

up the bulk of liquid using pumps or a vacuum truck for potential recovery and return to the appropriate container. Absorb the remaining liquid using sand or a commercial absorbent; dispose as non-hazardous solid waste. Flush the spill area with water and collect the rinsates for disposal or sewer as appropriate.

Water Spill: Wear recommended protective equipment and clothing if contact with hazardous

material can occur. Stop or divert water flow. Dike contaminated water and remove for disposal and or treatment. As appropriate, notify all downstream

users of possible contamination.

Disposal: Laws and regulations for disposal vary widely by locality. Observe all

applicable regulations and laws. This material may be disposed of in solid waste in a manner similar to other nuisance dust materials. Disposal in sanitary

landfill is usual but local regulations should be checked and observed.

Extinguishing Media: Large quantities of water. In case of a fire in close proximity, all means of

extinguishing are acceptable. Self-contained breathing apparatus or approved gas mask should be worn due to small particle size. Use extinguishing media appropriate for surrounding fire. Apply cooling water to sides to transport or storage vessels that are exposed to flames until the fire is extinguished. Do not

approach hot vessels that contain the product.

First Aid: After contact with skin, wash immediately with plenty of water and soap. In case

of contact with eyes, rinse immediately with plenty of water and seek medical

attention. Consult an ophthalmologist in all cases.

Section 8 - Special Protection or Handling

Storage: Store in a roofed and well-ventilated area in the unopened original package at ambient

temperature and pressure. Store in a cool, dry area away from incompatible materials

and products.

Protective Gloves: Vinyl or Rubber, neoprene nitrile butyl- rubber.

Eyes: Splash Goggles or Full Face Shield. Area should have approved means of washing eyes.

Ventilation: General exhaust.

Storage: Store in cool, dry, ventilated area.

Transportation: Not DOT regulated

Note: IMDG regulated

Protect from incompatible materials.

Section 9- Exposure Controls/Personal Protection

Control Measures: Use a local or general, mechanical exhaust ventilation system capable of

maintaining emissions, in the work area, below the ACGIH-TLV, OSHA-

PEL, or levels that may cause irritation.

Recommended Personal Protective Equipment:

Respirator: Respiratory protection is not normally required. However, for exposures above

the ACGIH-TLV or OSHA-PEL, wear a NIOSH approved full face piece or half mask air-purifying cartridge respirator equipped with a good mist/particulate

cartridge or supplied air.

Eyes: Wear chemical goggles (recommended by ANSI Z87.1-1979), unless a full

face piece respirator is worn.

Clothing & Equipment: If splashing or contact is likely, wear a Neoprene or Natural Rubber apron

when handling this product. An eye wash station and safety shower should

be available in the work area.

Footwear: If contact is likely, wear Neoprene or Natural Rubber boots.

Section 10- Toxicology

Data on this material and/or similar material are summarized below.

Acute toxicity:

Oral: No more than slightly toxic. Rat LD50> 2,000 mg/kg
Dermal: No more than slightly toxic. Rat LD50> 2,000 mg/kg

Reported Human Effects: No human toxicity studies have been carried out with this product. Due to the physical nature of this product, may cause eye, skin and respiratory irritation.

Section 11- Ecological Information

Environmental Fate: No data available.

Ecotoxicology: Data on this material and/or similar are summarized below.

Aquatic toxicity data: Practically nontoxic. LC50 > 100 mg/L (dispersion)

Section 12-Regulatory Information

Carcinogenic Potential:

Regulated by OSHA: No Listed on NTP Report: No

Listed by IARC: No IARC Group: NA

ACGIH Appendix A: Not listed A 1 Confirmed Human: NA A 2 Confirmed Human: NA

US EPA Requirements:

Release Reporting CERCLA (40 CFR 302)

Listed Substance: Not listed

Reportable Quantity: NA Category: NA

RCRA Waste No. NA Unlisted Substance: NA Reportable Quantity: NA

Characteristic: NA RCRA Waste No: NA

SARATITLE III

Section 302 & 303 (40 CFR 355)

Listed Substance: Not listed Reportable Quantity: NA Planning Threshold: NA

Section 311 & 312 (40 CFR 370)

Hazard Categories: Fire: N Sudden Release of Pressure: N Reactive: N

Acute Health: Y Chronic Health: N Planning threshold: 10,000 pounds

Section 313 (40 CFR 372)

Listed Toxic Chemical: Not listed

Planning Threshold: NA

US TSCA Status

Listed (40 CFR 710): Yes

State Regulations: State of California: Safe Drinking Water and Toxins Enforcement Act.

1986 (Proposition 65)

Carcinogen: No

Reproductive Toxin: No

State Right to Know Laws: NJ, PA, CA

Section 13-Disposal Considerations

Waste Disposal: Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Section 14 - Other Information

Materials containing reactive chemicals should be used only by personnel with appropriate chemical training. This product is not formulated to contain any substances which the State of California has found to cause cancer and/or birth defects or other reproductive harm.

Martin Engineering provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using the product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

MARTIN ENGINEERING MAKES NO REPRESENTATIONS OR WARRANTIES EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MARTIN ENGINEERING WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.



Martin Engineering USA
One Martin Place
Neponset, IL 61345-9766 USA
800 544 2947 or 309 852 2384
Fax 800 814 1553
www.martin-eng.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001:2008 =