Castrol Industrial Central Inc.

MATERIAL SAFETY DATA SHEET

Emergency Phone No.: (312) 454-1000 Information Phone No.: (312) 454-1000 FIRE
1
HEALTH 2 0 REACTIVITY
0
SPECIAL

REVISED: 07/10/1991

1. MATERIAL IDENTIFICATION

PRODUCT TRADE NAME: CASTROL TARP MANUFACTURER: Castrol Industrial Central Inc.

ADDRESS: 630 W. Washington Blvd. Chicago IL, 60661

MFG. FACILITY ADDRESS: 149 S. Grant Street North Aurora 1L, 60542

Preparer: K. Gritenas

Preparation Date: 03/01/1991

	INGREDIENTS	
11.		

MATERIAL OR COMPONENTS	x	CAS No.	TLV (ACGIH)	PEL (OSHA)
2,4-Pentanediol, 2-methyl	1-5	107-41-5	(C)=125 mg/M3	(C)=125 mg/M3
Sulfonic acids, petroleum, barium salts	1-5	61790-48-5	0.5mg/M3 for Ba	0.5mg/M3 for Ba
Distillates (petroleum), hydrotreated light	1-5	64742-47-8	not established	not established
Distillates (petroleum), hydrotreated heavy naphthenic	10-30	64742-52-5	5 mg/M3 (mist)	5 mg/M3 (mist)
Distillates (petroleum), hydrotreated light naphthenic	50-70	64742-53-6	5 mg/M3 (mist)	5 mg/M3 (mist)

Contains no other ingredients now known to be hazardous as defined by OSHA 29 CFR 1910.1000 (subpart z) and OSHA CFR 29 1910.1200.

III. PHYSICAL PROPERTIES

APPEARANCE & ODOR: Hazy brown thixotropic, liquid at 150 F

BOILING POINT 'F ('C): NA NA
MELTING POINT 'F ('C): NA NA
SPECIFIC GRAVITY (H20=1): 0.887 ± 0.2

VAPOR PRESSURE: NA

VAPOR DENSITY (AIR=1): NA

EVAPORATION RATE (BUTYL ACETATE=1): < 1

XVOLATILES BY VOLUME: 0

SOLUBILITY IN H20: Insoluble

PH AS IS: NA

pH (DILUTE): NA

90%

IV. FIRE AND EXPLOSION HAZARDS

FLASHPOINT

(method used)

> 200 'F 'C COC

FLAMMABLE LIMITS

LEL NA UEL NA

EXTINGUISHING MEDIA:

carbon dioxide, dry chemical, foam.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self contained breathing apparatus when fire fighting in a confined space. Cool fire exposed containers with waterspray to prevent rupture.

UNUSUAL FIRE & EXPLOSION HAZARDS:

None known.

CONTAINER HANDLING: DO NOT CUT OR WELD EMPTY DRUMS UNLESS THOROUGHLY CLEANED.

MSDS NUMBER: TARP

V. REACTIVITY DATA

STABILITY: Stable- normal conditions

CONDITIONS TO AVOID: None known.

INCOMPATIBILITIES: Strong oxidizing agents

HAZARDOUS DECOMPOSITION: Potential combustion products are oxides of C, N, sulfur and barium.

HAZARDOUS POLYMERIZATION: Will Not Polymerize

VI. HEALTH HAZARD SUMMARY

ROUTES OF EXPOSURE AND EFFECTS OF OVEREXPOSURE

FYES.

Concentrate will cause eye irritation.

SKIN ABSORPTION:

No acute effects expected.

SKIN CONTACT:

Concentrate may cause skin irritation.

INHALATION:

TLV for product not established. Refer to Hazardous Materials List for ingredient TLV's.

INGESTION:

Oral LD50 not established. Do not ingest.

CHRONIC EFFECTS:

Prolonged or repeated contact with petroleum oil may remove natural oils and fats from the skin.

THRESHOLD LIMIT VALUE: Not established for product

CONTAINS KNOWN CARCINOGENS: no

NTP: no IARC: no OSHA: no

EMERGENCY AND FIRST AID PROCEDURES

EYES:

In case of contact, flush eyes with plenty of water. Get medical attention if irritation persists.

SKIN

Wash skin with soap and water. If irritation occurs, get medical attention. Wash clothing before reuse.

INHALATION:

If respiratory discomfort or irritation occurs, move the person to fresh air. See a doctor if discomfort or irritation continues.

INGESTION:

Do not induce vomiting; get medical attention immediately.

VII. CONTROL MEASURES

DESDIBATORY PROTECTION.

Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the threshold limit value (TLV) or permissible exposure limit (PEL). If any associated TLV or PEL is exceeded, provide NIOSH approved respiratory protection.

GLOVES:

Impervious gloves such as rubber should be used when handling this product.

FYE PROTECTION:

Safety glasses with side shield or chemical goggles.

OTHER.

Eyewash facility. Appropriate clothing to avoid skin contact.

VIII. PRECAUTIONS

CONTAINMENT PROCEDURES:

Recover free liquid. Keep product out of streams and waterways by diking or impounding. Advise authorities if product has entered o may enter sewers, watercourses or extensive land areas.

WASTE DISPOSAL PROCEDURES:

Dispose of in accordance with local, state and federal regulations. Disposal of this material to the land may be banned by federal law (40 CFR 268).

STORAGE AND HANDLING PROCEDURES:

Avoid contact with skin and eyes. Avoid breathing mists. Do not take internally. Keep container closed when not in use. Bring product to room temperature before use. Do not store near heat, flame or strong oxidizing agents.

RCRA HAZARDOUS WASTE DESIGNATION:

This product contains barium and therefore may fall under current EPA RCRA definitions of hazardous waste with designation D005 because of toxicity if the product is disposed of in its original form.

CERCLA REPORTABLE QUANTITY:

This product does not contain any CERCLA regulated materials.

IX. OTHER HAZARD INFORMATION

The various suppliers of the solvent (CAS No. 64742-47-8) used in this product recommend TLV's ranging from 350 mg/M3 to 2100 mg/M3. According to the suppliers, neither OSHA nor ACGIH have established limits for the solvent.

PETROLEUM OIL: STEL = 10 mg/M3. Using terminology of the International Agency for Research on Cancer (IARC), the petroleum distillates listed in Section II are classified by the supplier as severely processed. Not all those listed in Section II may be present. The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200.

Alkanolamine

This product contains an alkanolamine. In all metalworking fluids containing amines, there is a potential for forming nitrosamines which are animal carcinogens. Therefore, no nitrites or related nitrosating agents should be added to such compositions.

MSDS NUMBER: TARP

X. ADDITIONAL REGULATORY INFORMATION

OCCUPATIONAL SAFETY and HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.1200 Hazardous Chemical: ves

SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA)

Section 302, Extremely Hazardous Substance: no

Section 311. Hazardous Chemical: yes

Immediate: yes Delayed: yes Fire: no Sudden Release: no Reactive: no

Section 313, Toxic Chemical: no

Barium compounds, 1-5%

TOXIC SUBSTANCES CONTROL ACT (TSCA)

This product is a mixture and is NOT listed in the TSCA Inventory. The individual ingredients in the product are listed in the TSCA Inventory.

DEPARTMENT OF TRANSPORTATION (DOT)

PROPER SHIPPING NAME: Not regulated

HAZARD CLASS (49 CFR 172.101): Not regulated

HAZARD ID NUMBER: Not regulated

DISCLAIMER

Information presented herein has been compiled from information provided to us by our suppliers and other sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or the use of any product in violation of any patent or in violation of any law or regulation. It is the users' responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

MSDS NUMBER: TARP