

## MATERIAL SAFETY DATA SHEET

HEALTH 2 0 REACTIVITY

Emergency Phone No.: (708) 241-4000

Information Phone No.: (708) 241-4000

SPECIAL

## I. MATERIAL IDENTIFICATION

PRODUCT TRADE NAME: TARP

MANUFACTURER: CASTROL INDUSTRIAL INC.

ADDRESS: 1001 WEST 31ST STREET DOWNERS GROVE IL, 60515-1280

MFG. FACILITY ADDRESS:

Preparer: K. Gritenas

Preparation Date: 08/30/1993

## II. HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	%	CAS No.	TLV (ACGIH)	PEL (OSHA)
Distillates (petroleum), hydrotreated heavy naphthenic	20-25	64742-52-5	5 mg/M3 (mist)	5 mg/M3 (mist)
Distillates (petroleum), hydrotreated light naphthenic	55-60	64742-53-6	5 mg/M3 (mist)	5 mg/M3 (mist)
2,4-Pentanediol, 2-methyl	1-5	107-41-5	(C)=125 mg/M3	(C)=125 mg/M3
Sulfonic acids, petroleum, barium salts	1-5	61790-48-5	0.5mg/M3 for Ba	0.5mg/M3 for Ba

Contains no other ingredients now known to be hazardous as defined by OSHA 29 CFR 1910.1000 (subpart z) and OSHA CFR 29 1910.1200.

## III. PHYSICAL PROPERTIES

APPEARANCE &amp; ODOR: Hazy brown thixotropic, liquid at 150 F

BOILING POINT 'F ('C): NA NA

MELTING POINT 'F ('C): NA NA

SPECIFIC GRAVITY (H2O=1): 0.870 - 0.940

VAPOR PRESSURE: NA

VAPOR DENSITY (AIR=1): NA

EVAPORATION RATE (BUTYL ACETATE=1): &lt; 1

%VOLATILES BY VOLUME: 0

VOC: 000.00 g/L 00.000 lbs/gallon

SOLUBILITY IN H2O: Insoluble

pH AS IS: NA

pH (DILUTE): NA @ 0 %

VOC not yet determined  
for this product.

## IV. FIRE AND EXPLOSION HAZARDS

FLASHPOINT (method used)

&gt; 200 'F 'C COC

FLAMMABLE LIMITS

LEL NA UEL NA

EXTINGUISHING MEDIA:

carbon dioxide, dry chemical, foam.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self contained breathing apparatus when fire fighting in a confined space. Cool fire exposed containers with waterspray to prevent rupture.

UNUSUAL FIRE &amp; EXPLOSION HAZARDS:

None known.

CONTAINER HANDLING: DO NOT CUT OR WELD EMPTY DRUMS UNLESS THOROUGHLY CLEANED.

MSDS NUMBER: tarp

REVISED: 10/21/1994

---

V. REACTIVITY DATA

---

STABILITY: Stable- normal conditions

CONDITIONS TO AVOID: None known.

INCOMPATIBILITIES: Strong oxidizing agents

HAZARDOUS DECOMPOSITION: Potential combustion products are oxides of C, N, sulfur and barium.

HAZARDOUS POLYMERIZATION: Will Not Polymerize

---

VI. HEALTH HAZARD SUMMARY

---

ROUTES OF EXPOSURE AND EFFECTS OF OVEREXPOSURE

EYES:

Concentrate will cause eye irritation.

SKIN ABSORPTION:

No acute effects expected.

SKIN CONTACT:

Concentrate may cause skin irritation.

INHALATION:

TLV for product not established. Refer to Hazardous Materials List for ingredient TLV's.

INGESTION:

Oral LD50 not established. Do not ingest.

CHRONIC EFFECTS:

Prolonged or repeated contact with petroleum oil may remove natural oils and fats from the skin.

THRESHOLD LIMIT VALUE: Not established for product

CONTAINS KNOWN CARCINOGENS: no          NTP: no    IARC: no    OSHA: no

EMERGENCY AND FIRST AID PROCEDURES

EYES:

In case of contact, flush eyes with plenty of water. Get medical attention if irritation persists.

SKIN:

Wash skin with soap and water. If irritation occurs, get medical attention. Wash clothing before reuse.

INHALATION:

If respiratory discomfort or irritation occurs, move the person to fresh air. See a doctor if discomfort or irritation continues.

INGESTION:

Do not induce vomiting; get medical attention immediately.

---

## VII. CONTROL MEASURES

---

### RESPIRATORY PROTECTION:

Good industrial hygiene practices recommend that engineering controls be used to reduce environmental concentrations to the threshold limit value (TLV) or permissible exposure limit (PEL). If any associated TLV or PEL is exceeded, provide NIOSH approved respiratory protection.

### GLOVES:

Impervious gloves such as rubber should be used when handling this product.

### EYE PROTECTION:

Safety glasses with side shield or chemical goggles.

### OTHER:

Eyewash facility. Appropriate clothing to avoid skin contact.

---

## VIII. PRECAUTIONS

---

### CONTAINMENT PROCEDURES:

Recover free liquid. Keep product out of streams and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas.

### WASTE DISPOSAL PROCEDURES:

Dispose of in accordance with local, state and federal regulations. Disposal of this material to the land may be banned by federal law (40 CFR 268).

### STORAGE AND HANDLING PROCEDURES:

Avoid contact with skin and eyes. Avoid breathing mists. Do not take internally. Keep container closed when not in use. Bring product to room temperature before use. Do not store near heat, flame or strong oxidizing agents.

### RCRA HAZARDOUS WASTE DESIGNATION:

This material is regulated as used oil by the EPA. Under the Used Oil Management Standards (40 CFR 279) effective 3/8/93, EPA presumes used oil will be recycled. If it is, no characteristic determination is required provided all parties handling the used oil comply with part 279. These management standards apply to used oil until it is disposed of or sent for disposal. At disposal this product may exceed TCLP limits for barium (D005). State regulations may differ from federal ones. Refer to local regulations also.

### CERCLA REPORTABLE QUANTITY:

This product does not contain any CERCLA regulated materials.

---

## IX. OTHER HAZARD INFORMATION

---

The various suppliers of the solvent used in this product recommend TLV's ranging from 350 mg/M<sup>3</sup> to 2100 mg/M<sup>3</sup>. According to the suppliers, neither OSHA nor ACGIH have established limits for the solvent.

**PETROLEUM OIL:** STEL = 10 mg/M<sup>3</sup>. Using terminology of the International Agency for Research on Cancer (IARC), the petroleum distillates listed in Section II are classified by the supplier as severely processed. Not all those listed in Section II may be present. The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200.

### Alkanolamine

This product contains an alkanolamine. In all metalworking fluids containing amines, there is a potential for forming nitrosamines which are animal carcinogens. Therefore, no nitrites or related nitrosating agents should be added to such compositions.

---

---

X. ADDITIONAL REGULATORY INFORMATION

---

OCCUPATIONAL SAFETY and HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.1200 Hazardous Chemical: yes

SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA)

Section 302, Extremely Hazardous Substance: no

Section 311, Hazardous Chemical: yes

Immediate: yes Delayed: yes Fire: no Sudden Release: no Reactive: no

Section 313, Toxic Chemical: yes

Barium compound, 2%

TOXIC SUBSTANCES CONTROL ACT (TSCA)

This product is a mixture and is NOT listed in the TSCA Inventory. The individual ingredients in the product are listed in the TSCA Inventory.

DEPARTMENT OF TRANSPORTATION (DOT)

PROPER SHIPPING NAME: Environmentally hazardous substances, liquid, N.O.S. (contains barium), 9,  
UN3082, PG III

HAZARD CLASS (49 CFR 172.101):

HAZARD ID NUMBER:

FREIGHT CLASS

NMFC 155250, PETROLEUM OILS, GREASES & RELATED PRODUCTS, NOI CLASS 65

---

DISCLAIMER

Information presented herein has been compiled from information provided to us by our suppliers and other sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or the use of any product in violation of any patent or in violation of any law or regulation. It is the users' responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

---