

CLEANER

SECTION 1 IDENTITY OF MATERIAL
 Trade Name: OATEY CLEANER
 Product Numbers: 30766, 30779, 30782, 30795, 30805
 Formula: Organic Solvents
 Synonyms: Methyl Ethyl Ketone, Cyclohexanone, Acetone and Tetrahydrofuran
 Firm Name & Mailing Address: OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland, Ohio 44135, U.S.A. <http://www.oatey.com>
 Oatey Phone Number: (216) 267-7100
 Emergency Phone Numbers: For Emergency First Aid call 1-303-623-5716 COLLECT. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300

SECTION 2 COMPOSITION

<u>INGREDIENTS:</u>	<u>%:</u>	<u>CAS NUMBER:</u>	<u>ACGIH TLV TWA:</u>	<u>OSHA PEL TWA:</u>	<u>OTHER:</u>
Acetone	20 - 40%	67-64-1	500 ppm 750 ppm STEL	1000 ppm	
Methyl Ethyl Ketone	60 - 80%	78-93-3	200 ppm	200 ppm	

SECTION 3 EMERGENCY OVERVIEW

Clear liquid with an ether-like odor. Extremely flammable liquid and vapor. Vapors may cause flash fire. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects. Swallowing may cause irritation, nausea, vomiting, diarrhea and kidney or liver disorders. Aspiration hazard. May be fatal if swallowed. Symptoms may be delayed.
 NFPA Hazard Signal: Health: 1 Stability: 0 Flammability: 3 Special: None
 HMIS Hazard Signal: Health: 3 Stability: 0 Flammability: 3 Special: None
 OSHA Hazard Classification: Flammable, irritant, organ effects
 Canadian WHIMS Classification: Class B, Division 2; Class D, Division 2, Subdivision B

SECTION 4 EMERGENCY AND FIRST AID PROCEDURES - CALL 1-303-623-5716 COLLECT

Skin: Remove contaminated clothing immediately. Wash all exposed areas with soap and water. Get medical attention if irritation develops. Remove dried cement with Oatey Plumber's Hand Cleaner or baby oil.
Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with water for 15 minutes. If irritation persists, seek medical attention.
Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.
Ingestion: DO NOT INDUCE VOMITING. Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

CLENER**SECTION 5 FIRE FIGHTING MEASURES**

Flashpoint / Method: 0 - 9 Degrees F. / PMCC

Flammability: LEL = 1.8 % Volume, UEL = 11.5 % Volume

Extinguishing Media: Use dry chemical, CO2, or foam to extinguish fire. Cool fire exposed container with water. Water may be ineffective as an extinguishing agent.

Special Fire Fighting Procedure: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored

Unusual Fire and Explosion Hazards: Extremely flammable liquid. Keep away from heat and all sources of ignition including sparks, flames, lighted cigarettes and pilot lights. Containers may rupture or explode in the heat of a fire. Vapors are heavier than air and may travel to a remote ignition source and flash back.

Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Remove all sources of ignition and ventilate area. Stop leak if it can be done without risk. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up spill with an inert absorbent such as sand, earth or other non-combusting material. Put absorbent material in covered, labeled metal containers. Prevent liquid from entering watercourses, sewers and natural waterways. Report releases to authorities as required. See Section 12 for disposal information.

SECTION 7 HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation (equivalent to outdoors). Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

Storage: Store in a cool, dry, well-ventilated area away from incompatible materials. Keep containers closed when not in use.

Other: "Empty" containers retain product residue and can be hazardous. Follow all MSDS precautions in handling empty containers. Do not cut or weld on or near empty or full containers.

SECTION 8 ECOLOGICAL INFORMATION

This product is not expected to be toxic to aquatic organisms. Methyl Ethyl Ketone: 96 hour LC50 for fish is greater than 100 mg/L. Acetone: 96 hour LC50 for fish is greater than 100 mg/L.

VOC Information: This product emits VOC's (volatile organic compounds) in its use. Make sure that use of this product complies with local VOC emission regulations, where they exist.

VOC Level: 600 g/l per SCAQMD Test Method 316A.

CLEANER**SECTION 9 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ventilation: Open doors & windows. Provide ventilation capable of maintaining emissions at the point of use below recommended exposure limits. If used in enclosed area, use exhaust fans. Exhaust fans should be explosion-proof or set up in a way that flammable concentrations of solvent vapors are not exposed to electrical fixtures or hot surfaces.

Respiratory Protection: For operations where the exposure limit may be exceeded, a NIOSH approved organic vapor respirator or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Skin Protection: Rubber gloves are suitable for normal use of the product. For long exposures product chemical resistant gloves may be required such as 4H(tm) or Silver Shield(tm) to avoid prolonged skin contact.

Eye Protection: Safety glasses with sideshields or safety goggles.

Other: Eye wash and safety shower should be available.

SECTION 10 PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 133 Degrees F / 56 C

Melting Point: N/A

Vapor Pressure: 186 mmHg @ 20 Degrees C

Vapor Density: (Air = 1) 2.0

Volatile Components: 100%

Solubility In Water: Negligible

pH: N/A

Specific Gravity: 0.79 +/- 0.02

Evaporation Rate: (BUAC = 1) = 7.7

Appearance: Colorless Liquid

Odor: Ether-Like

Will Dissolve In: Organic solvents

Material Is: Liquid

SECTION 11 STABILITY AND REACTIVITY

Stability: Stable.

Conditions To Avoid: Avoid heat, sparks, flames and other sources of ignition.

Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

Incompatibility/ Materials To Avoid: Oxidizing agents, alkalies, amines, ammonia, acids, chlorine compounds, chlorinated inorganics (potassium, calcium and sodium hypochlorite) and hydrogen peroxides. May attack plastic, resins and rubber.

Hazardous Polymerization: Will not occur.

SECTION 12 DISPOSAL INFORMATION

Waste Disposal: Dispose in accordance with current local, state and federal regulations.

CLEANER**SECTION 13****TOXICOLOGICAL INFORMATION****Inhalation:**

Vapors or mists may cause mucous membrane and respiratory irritation, coughing, headache, dizziness, dullness, nausea, shortness of breath and vomiting. High concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.

Skin:

May cause irritation with redness, itching and pain. Methyl ethyl ketone may be absorbed through the skin causing effects similar to those listed under inhalation.

Eye:

Vapors may cause irritation. Direct contact may cause irritation with redness, stinging and tearing of the eyes. May cause eye damage.

Ingestion:

Swallowing may cause abdominal pain, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.

Chronic

Prolonged or repeated overexposure cause dermatitis and damage to the kidney, liver, lungs and central nervous system.

Toxicity:**Toxicity Data:****Acetone:**

Oral rat LD50: 5,800 mg/kg

Inhalation rat LC50: 50,100 mg/m³/8 hours

Methyl Ethyl Ketone:

Oral rat LD50: 2,737 mg/kg

Inhalation rat LC50: 23,500 mg/m³/8 hours

Skin rabbit LD50: 6,480 mg/kg

Sensitization:

None of the components are known to cause sensitization.

Carcinogenicity:

None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.

Mutagenicity:

Acetone has been positive in a mammal cell cytogenic analysis but negative in many other assays. At most, acetone is weakly genotoxic. Methyl ethyl ketone is not considered genotoxic based on laboratory studies.

Reproductive**Toxicity:**

Methyl ethyl ketone has been shown to cause embryofetal toxicity and birth defects in laboratory animals. Acetone has been found to cause adverse developmental effects only when exposure levels cause other toxic effects to the mother.

Medical**Conditions****Aggravated By****Exposure:**

Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.

CLEANER

SECTION 14 TRANSPORTATION INFORMATION

DOT Less than 1 Liter (0.3 gal) Greater than 1 Liter (0.3 gal)

Proper Shipping Name: Consumer Commodity Adhesives
 Hazard Class/Packing Group: ORM-D 3, PG11
 UN/NA Number: None UN1993
 Hazard Labels: None Flammable Liquid

IMDG
 Proper Shipping Name: Flammable Liquid, N.O.S. Flammable Liquid, N.O.S.
 Hazard Class/Packing Group: 3, 11 3, 11
 UN Number: UN1993 UN1993
 Label: None (Limited Quantities are excepted from labeling) Class 3 (Flammable Liquid)

RCRA Hazardous Waste Number: U002, U159
 EPA Hazardous Waste ID Number: D001, D035, F003, F005
 EPA Hazard Waste Class: Ignitable Waste. Toxic Waste (Methyl Ethyl Ketone content)
 2000 North American Emergency Response Guidebook Number: 127 or 128

SECTION 15 REGULATIONS

Hazard Category for Section 311/312: Acute Health, Chronic Health, Flammable

Section 302 Extremely Hazardous Substances (TPQ): This product does not contain chemicals regulated under SARA Section 302.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

Chemical	CAS #	%
Methyl Ethyl Ketone	78-93-3	60-80%

ERCLA 103 Reportable quantity: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Methyl Ethyl Ketone (80% maximum) of 5,000 lbs, is 6,250 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

California Proposition 65: This product contains trace amounts of chemicals known to the State of California to cause cancer. Under normal use conditions, exposures to these chemicals at levels above the State of California "No Significant Risk Level" (NSRL) are unlikely. Datey strongly encourages the use of proper personal protective equipment (PPE) and ventilation guidelines noted in Section 9 to minimize exposure to these chemicals.

TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

SECTION 16 DISCLAIMER

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, Datey cannot give guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.