

SEP-21-1999 16:28
MAY-17-1999 14:51

HEALTH SERVICES
BLUE CORAL/SLICK 50

713 546 4876 P.01
12166418617 P.04/07

15483

BLUE CORAL/SLICK 50
5300 HARVARD AVENUE
CLEVELAND, OH 44105

43712012new

**MATERIAL SAFETY
DATA SHEET**

IDENTITY (As Used on Label and List) One Lube Aerosol	STOCK NUMBER 43712012
--	--------------------------

SECTION I

MANUFACTURER'S NAME Blue Coral/Slick 50	EMERGENCY TELEPHONE NUMBER (216) 641-5490
ADDRESS (Number, Street, City, State, and ZIP Code) 5300 Harvard Avenue	TELEPHONE NUMBER FOR INFORMATION (216) 641-5490
Cleveland, OH 44105	DATE PREPARED 6/30/98
	SIGNATURE OF PREPARER (Optional)

SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	% OPTIONAL
Petroleum Oil, Paraffinic Oil	64742-65-0	5.0 MG/M3	(mist)	>50
Heptane	142-32-5	400PPM	400PPM	10-25
Carbon Dioxide	124-38-9	10,000PP	5000PPM	2

SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT 208 F -500 F	SPECIFIC GRAVITY (H20 = 1) 0.83
VAPOR PRESSURE (mm Hg.) N/A	MELTING POINT N/A
VAPOR DENSITY (AIR = 1) >1	EVAPORATION RATE (Butyl Acetate = 1) Slower than ether
SOLUBILITY IN WATER Nil	PH N/A

APPEARANCE AND ODOR
Aerosol Product

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used) 18 F YCC	FLAMMABLE LIMITS	LEL 1	UEL 10
---------------------------------------	------------------	----------	-----------

EXTINGUISHING MEDIA
Carbon dioxide, dry chemical, and or foam.

SPECIAL FIRE FIGHTING PROCEDURES
Closed containers may explode from internal pressure build up when exposed to extreme heat and discharge contents.
Vapor accumulation can flash or explode if ignited.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Water may be ineffective - water may be used to keep fire exposed containers cool.

SECTION V: REACTIVITY DATA

STABILITY	UNSTABLE	STABLE	CONDITIONS TO AVOID
		X	Application to hot surfaces. Exposure to open flame. Storage above 120°F.

INCOMPATIBILITY (Materials to Avoid)

Applications to hot surfaces. Storage above 120 F. Exposure to open flame. Strong Oxidizers

43712012new

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide.

HAZARDOUS	MAY OCCUR	WILL NOT OCCUR	CONDITIONS TO AVOID
POLYMERIZATION		X	None known to Blue Coral/Slick 50.

SECTION VI: HEALTH HAZARD DATA**HEALTH HAZARD (Acute or Chronic)**

Eye irritant, possible skin irritant.

SIGNS AND SYMPTOMS OF EXPOSURE

Respiratory irritation, headache, nausea, fatigue, drowsiness, impaired coordination.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Skin contact may dry skin and irritate.

EMERGENCY AND FIRST AID PROCEDURES**SKIN CONTACT:** Wash skin with soap and water.**EYE CONTACT:** Remove contact lenses and flush eye for 15 minutes, if irritation persists contact physician.**INHALATION:** Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing.**INGESTION:** Do NOT induce vomiting. Call Physician immediately.**SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition, ventilate area, avoid breathing vapors and remove with inert absorbent.

WASTE DISPOSAL METHOD

Do not incinerate. Apply inert absorbent, place in closed containers and dispose of according to Local, State and or Federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store and use in cool, dry, well-ventilated areas. Do not store above 120°F. Aerosol level 3.

OTHER PRECAUTIONS

Keep away from children. Do not puncture or incinerate.

SECTION VIII: CONTROL MEASURES**RESPIRATORY PROTECTION (Specify Type)**

If personal exposure cannot be controlled below applicable limits by ventilation wear a properly fitted respirator approved by NIOSH MSHA for protection.

VENTILATION	LOCAL EXHAUST	MECHANICAL (General)
	Recommended	N/A
	SPECIAL	OTHER
		N/A
PROTECTIVE GLOVES	EYE PROTECTION	OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Recommended: solvent-resistant	Safety glasses	N/A

WORK/HYGIENIC PRACTICES

Do not store near food or drink. Wash exposed skin for hygienic purposes.

SECTION IX: UNIFORM HANDLING AND SHIPPING INFORMATION

Do not store above 120°F. Keep at room temperature as exposure to direct sunlight or heat may cause bursting.

	HMS	NFPA	DOT PROPER SHIPPING NAME	ORM-D consumer commodity
Health	1	1	DOT HAZARD CLASS	N/A
Flammability	2	2	DOT I.D. NUMBER	N/A
Reactivity	0	0	IATA PROPER SHIPPING NAME	Aerosols, Flammable, N.O.S. class 2, 1, UN 1950
		None	IATA HAZARD CLASS	2.1
Hazardous Rating Key:		IMO NUMBER		N/E

0= Insignificant; 1= Slight; 2=Moderate; 3= High; 4= Extreme

(1) Hazardous materials identification system (National paint and coating association) rating applies to product "as packaged" ambient temperature.

(2) National fire protection association rating identifies the severity of hazardous of material during a fire emergency i.e. "on fire"