



224 SW 153rd St.
Mailbox 937
Burien, WA 98166

206/248-0400 (PH)
206/248-6593 (FAX)

FAX COVER LETTER

TO: JASON DATE: 6/28/04
FROM: GRETCHEN FAX#: 309/594-2432 PGS INCL COVER: 2
RE: MSDS - ANCHORING CEMENT
MESSAGE: SEE ATTACHED

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY

PAKMIX Anchoring Cement

N.F.P.A. & H.M.I.S. RATING**HAZARD INDEX**

4 = Severe
 3 = Serious
 2 = Moderate
 1 = Slight
 0 = Minimal

HAZARD CLASS

Flammability
 0
 Health Reactivity
 1 0
 Special Note

SECTION I - MANUFACTURER

US Mix Products Co.
 112 S. Santa Fe Dr.
 Denver, CO 80223

Emergency Contact
 303-778-7227
 Information Contact
 303-778-7227

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT
Mineral fillers	5 mg/m ³	15 mg/m ³		10-20
Free SiO ₂	10 mg/m ³	5 mg/m ³		2

None of the components of the mixture are considered Hazardous Material or carcinogens (1910.1200 Hazard Communication (4)(4).

TRANSPORTATION INFORMATION

NA

SECTION III - PHYSICAL CHEMICAL CHARACTERISTICS

Boiling Point: NA	Specific Gravity (H ₂ O=1): 2.2
Vapor Pressure (mm Hg): NA	Melting Point: NA
Vapor Density (Air = 1): NA	Evaporation (Butyl Acetate = 1): NA
Solubility: Negligible	Appearance: Powder

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Tag Closed Cup): NA
 Flammable Limits: NA
 Extinguishing Media: NA
 Special Fire Fighting Procedures: NA
 Unusual Fire and Explosion Hazards: NA

SECTION V - REACTIVITY DATA

Stability: Stable
 Conditions to Avoid: None
 Incompatibility (Materials to Avoid): None