

MATERIAL SAFETY DATA SHEET

Product Name: Emergency Assistance:
 Distributing Products 1-800-488-6117
 Street HMIS Hazard Rating:
 Chicago, Illinois 60409

FIRE=0 Least=0
 HEALTH=1 Slight=1
 REACTIVITY=1 Moderate=1
 0.996 PERSONAL PROTECTION=B High=3
 Revised 18, 2001 Extreme=4

Synonyms:

WALLPAPER GH-34
 209820, 209822
 Other Synonyms: Vinyl Wallcovering Adhesive
 Vegetable based adhesive

Hazardous Ingredients/Identity Information

Chemical Name(s)	OSHA PEL	ACGIH TLV	max %
No Hazardous Ingredients			

Physical/Chemical Characteristics

Appearance: Off-white viscous paste, Mild, slight soap odor
 Specific Gravity (water=1): 1.04
 Density by Weight: approx. 15
 Density by Volume: approx. 12
 Solubility in Water: Miscible in all proportions
 Boiling Point: 212F
 Freezing Point: Same as water
 Vapor Pressure: Same as water
 Flash Point: Same as water
 Ignitability: n.a.
 VOC Content (VOC, less water): max 50 g/l; 0.42 lb/gal

Extinguishing Methods:
Special Fire Fighting Equipment
Self contained breathing
apparatus involving general
unusual Fire and Explosions

Section 5-Health Hazard

Page 2 of 3

PASTE FOR UNIFORMITY

Genotoxicity: NTP:non-carcinogenic
Pre-exposure--Under current conditions
considered non-hazardous.

Emergency First Aid Measures-
Eyes- Mild irritant. If irritation
persists, seek medical attention.
Skin- If contact occurs, wash with
water. Protective gloves may be
required. Irritants.

Inhalation- No hazardous effects
expected. If ingestion occurs,
do not induce vomiting. If
conscious person, seek medical attention.

Section 6-Reactivity Data

This product is stable under
normal conditions. It is
compatible with water. No
polymerization does not occur.

Section 7-Precautions for Use

Steps to be taken in case of
spillage: Containers of 1-2 gallons
may be washed down the drain. If
large spillage occurs, clean up
as soon as possible and disposed
of properly. Federal, State and
local regulations apply. This
product is a slip hazard, and
should be used with caution.

Section 8-Control Measures

Respiratory protection
is not required. Where this product is
used, adequate ventilation, such as
windows, exhaust fans, and
protective gloves and goggles.

temperatures (50-100 F). Prohibited for use on children. Keep containers closed.

is classified as a non-hazardous industrial waste.

PASTED WALLPAPER GH-34

is considered non-hazardous under 29CFR 1910.1200 (b)(1).

is a "controlled product" under the Hazardous Materials Information System (HMIS).

Properties

Flammable Class --- 60

Adhesive Class --- Adhesive Paste

is subject to the Community Right to Know (SARA Title III) provisions (40CFR 370).

is not a hazardous chemical under the provisions covered by Title III of the CERCLA (40CFR 372).

does not contain a chemical which is listed in the HCS concentrations.

302.4 (b) (1)

is not released to air, land or water in quantities that require notification to the Response Center under the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA).

is not on the list of chemicals under the Comprehensive Environmental Response, Compensation and Liability Act, Title III Section 304.

When it is a waste, it is classified as a non-hazardous industrial waste.

non-hazardous waste under criteria
and Recovery Act (40CFR 261).

Chemical Control Law Status

All components of this product are
Toxic Substance Control Act (TSCA) Ch

All components of this product are

Environmental Protection Act

(CFR 261)