

Lubricant

**BLUE CORAL/SLICK 50**  
**5300 HARVARD AVENUE**  
**CLEVELAND, OH 44105**

**MATERIAL SAFETY**  
**DATA SHEET**  
**43601055**

IDENTITY (as Used on Label and Label)	HS NUMBER
<b>Slick 50 One Lube</b>	<b>436 - 43712012, 4360412</b>

**SECTION I**

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NUMBER
<b>Blue Coral-Slick 50, Ltd.</b>	<b>(216) 641-5490</b>
ADDRESS (Number, Street, City, State, and ZIP Code)	TELEPHONE NUMBER FOR INFORMATION
<b>1215 Valley Belt Road</b>	<b>(216) 641-5490</b>
<b>Cleveland, OH 44131</b>	DATE PREPARED
	<b>8/25/98</b>
	SIGNATURE OF PREPARED (Optional)

**SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

HAZARDOUS INGREDIENTS	CAS NUMBER	CONC. BY WEIGHT	REGULATORY
<b>Petroleum Oil</b>	<b>64742-54-7</b>	<b>5.0 mg/100<sup>3</sup></b>	<b>90-96</b>
	<b>8002-05-9</b>	<b>N/E</b>	<b>N/E</b>
<b>Proprietary Chemicals</b>	<b>MIXTURE</b>		<b>4-5</b>

**SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS**

BOILING POINT	<b>640 F</b>	SPECIFIC GRAVITY (20 = 1)	<b>0.863</b>
VAPOR PRESSURE (mm Hg)	<b>N/E</b>	MELTING POINT	<b>N/E</b>
RELATIVE DENSITY (AIR = 1)	<b>&gt;1.0</b>	EVAPORATION RATE (Basis Acetate = 1)	<b>&lt;1.0</b>
SOLUBILITY IN WATER	<b>Negligible</b>	PH	<b>N/E</b>

**APPEARANCE AND ODOR****Hazy straw colored liquid.****SECTION IV: FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT (Method Used)	FLAMMABLE LIMITS	LEL	UEL
<b>230 F</b>		<b>N/E</b>	<b>N/E</b>

**EXTINGUISHING MEDIA****Foam, carbon dioxide and dry chemical.****SPECIAL FIRE FIGHTING PROCEDURES****Self-contained breathing supply.****UNUSUAL FIRE AND EXPLOSION HAZARDS****Use caution when handling around heat, sparks, pilot lights, static electricity or open flames.****SECTION V: REACTIVITY DATA**

STABILITY	UNSTABLE	STABLE	CONDITIONS TO AVOID
		<b>X</b>	

**INCOMPATIBILITY (Materials to Avoid)****Strong oxidizing materials.****HAZARDOUS DECOMPOSITION OR BY-PRODUCTS****Carbon dioxide and aldehydes.**

HAZARDOUS POLYMERIZATION	MAY OCCUR	WILL NOT OCCUR	CONDITIONS TO AVOID
		<b>X</b>	

**SECTION VI: HEALTH HAZARD DATA****HEALTH HAZARDS (Acute or Chronic)****Eye and skin irritant.****SIGNS AND SYMPTOMS OF EXPOSURE****Prolonged contact with skin may cause dermatitis or dry the skin.**

**MEDICAL CONDITIONS GENERALLY ANTICIPATED BY EXPOSURE**  
**None**

**EMERGENCY AND FIRST AID PROCEDURES**

**Eyes:** Flush with large amounts of water for 15 minutes or until irritation subsides.  
**Obtain medical assistance if irritation persists.**

**Skin:** Remove contaminated clothing and wash skin with soap and water.

**Ingestion:** DO NOT INDUCE VOMITING. Obtain medical assistance.

**Inhalation:** If exposed to vapor from hot product and overcome, remove from exposure to fresh air and obtain medical assistance.

**SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

**Recover free product. Add sand, earth or other suitable absorbent material to spill area.**

**Keep product out of sewers and water courses by diking and impounding.**

**WASTE DISPOSAL METHOD**

**Dispose of in accordance with Federal, State and Local regulations.**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

**Do not store below 150 F, keep away from high heat or flames.**

**DO NOT store in proximity of strong oxidizers; avoid contact with oxygen, calcium hypochlorite, sodium hypochlorite and chlorine.**

**OTHER PRECAUTIONS**

**KEEP AWAY FROM CHILDREN.**

**SECTION VIII: CONTROL MEASURES**

**RESPIRATORY PROTECTION (Specify Type)**

**Use local exhaust.**

VENTILATION	LOCAL EXHAUST	MECHANICAL (General)
	Recommended	None
PROTECTIVE GLOVES	SPECIAL	OTHER
	None	None
Chemical-resistant gloves.	EYE PROTECTION	OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Goggles	None required when used as intended.	

**WORKHYGIENIC PRACTICES**

**Use normal hygienic practices.**

**SECTION IX: UNIFORM HANDLING AND SHIPPING INFORMATION**

	HMIS	NFPA	DOT PROPER SHIPPING NAME	NONE
			DOT HAZARD CLASS	NA
Health	1	1	DOT I.D. NUMBER	NA
Flammability	1	1	IATA PROPER SHIPPING NAME	NONE
Reactivity	0	0	IATA HAZARD CLASS	NA
			IMO NUMBER	NA