Material Safety Data Sheet (MSDS)

Series: #0541, #0542, #0544, #0545, #0548 (All Labels)

NFPA Rating:

1-0-0

HMIS Rating:

1-0-0-B

SECTION I			EMERGENCY TELEPHONE NO		
TRADE NAME (IF NONE, PUT CHEMICAL)	ONETIME® Lightweight Spackling Compound		(918) 825-5744 (24 Hrs.)		
MANUFACTURER'S NAME AND TELEPHONE NO.	Red Devil, Incorporated	(918) 825-5744			
ADDRESS (Number, Street,	One Webb Street, Pryor, Okla	ahoma 74361			

%	TLV	PEL	UNITS
<50	NE	NE	
<2.0 <1.0 <30	50 NE NA	50 NE NA	ppm
-20	,,,_		
	<50 <2.0 <1.0	<50 NE <2.0 50 <1.0 NE <30 NA	<50 NE NE <2.0 50 50 <1.0 NE NE <30 NA NA

SECTION III - PHYSICAL DATA						
BOILING POINT (°F)	NE	SPECIFIC GRAVITY (H ₂ 0=1)	>1			
VAPOR PRESSURE (MM Hg.)	NE	PERCENT VOLATILES BY VOLUME (%)	<5			
VAPOR DENSITY (AIR=1)	<1	рН	9-9.5			
SOLUBILITY IN WATER	Appreciable	EVAPORATION RATE	<0.4 (BuAc = 1)			

APPEARANCE AND ODOR White paste; mild acrylic/ammonia odor

City, State, Zip Code)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA								
FLASH POINT (Method used)	None	FLAMMABLE LIMITS	LEL	NA	UEL	NA		
EXTINGUISHING MEDIA	Use media suitable for	adjacent materials.						
SPECIAL FIRE FIGHTING PROCEDURES	No special procedures are required.							
UNUSUAL FIRE AND EXPLOSION HAZARDS	None known.							

SECTION V - HEALTH HAZARD INFORMATION

SYMPTOM/EFFECTS OR OVEREXPOSURE

Inhalation of dust generated from dried product may cause respiratory irritation. Prolonged or repeated contact may cause mild skin and eye irritation.

FIRST AID

EYES

Immediately flush eyes with large amounts of water while holding eyelids open. Get medical attention if irritation persists.

SKIN

Wipe material from skin with cloth or paper towel, then wash exposed area with soap and water. Get medical help if irritation persists.

INHALATION

Move victim to fresh air and treat with artificial respiration if needed. Seek medical attention if irritation persists.

INGESTION

Contact local poison control center or physician IMMEDIATELY!!

SECTION VI - REACTIVITY DATA

STABILITY

Stable

INCOMPATIBLE MATERIALS

None known

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, carbon dioxide, acrylic acid

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES

Wipe up spilled material. Wash area with detergent.

WASTE DISPOSAL METHOD

Dispose of in accordance with Local, State and Federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY

Not normally required.

EYEWEAR

Wear safety glasses.

CLOTHING/GLOVES

Not normally required; in situations of extended skin contact, neoprene or other chemical resistant gloves are recommended.

VENTILATION

Provide adequate general dilution ventilation.

SECTION IX - SPECIAL PRECAUTIONS

Store in a closed container in cool dry area. Protect from freezing. This product contains ethylene glycol, an ingredient listed in Section 313 of SARA Title III.

Reviewed By: Larry G. Brandon January 29, 2002
NAME TITLE JANUARY 29, 2002

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.