

# BAHAMA BEIGE

V. A. SPAR CORPORATION  
MATERIAL SAFETY DATA SHEET

18232377  
PAGE 1  
37-00881R

CUSTOMER NAME : BORN PAINT CO

CUSTOMER NUMBER: 097382000

CUSTOMER INVOICE : 2329377

\*\*\*\*\* SECTION 1: PRODUCT IDENTIFICATION \*\*\*\*\*

MANUFACTURERS ADDRESS : 1104 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415  
MFG TELEPHONE NUMBER : 16121 332-7371  
24 HR EMERGENCY PHONE NO : 1-800-228-5635  
CHEMICAL NAME OR FAMILY : PAINT PRODUCT  
FORMULA : 00881R-122-A-09  
TRADE NAME : 37 891R VC HB EPY CURING AGT  
REVISION DATE : 05-16-92 DATE PRINTED : 06-15-92

\*\*\*\*\* SECTION 2: HAZARDOUS INGREDIENTS \*\*\*\*\*

NAME	APPROX WT %				
COMMON (NA): ALIPHATIC PETROLEUM DISTILLATES	5%	TLV TWA	NOT ESTAB		
		TLV STEL	NOT ESTAB		
CAS: 64742-88-7 CHEMICAL: SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.		OSHA PEL	500.00 PPM		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		
COMMON (NA): VM&P NAPHTHA	5%	TLV TWA	300.00 PPM		
		TLV STEL	NOT ESTAB		
CAS: 8030-30-6 CHEMICAL: NAPHTHA		OSHA PEL	NOT ESTAB		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		
COMMON (NA): TALC	40%	TLV TWA	2.00 MG/CU M		
		TLV STEL	NOT ESTAB		
CAS: 14807-96-6 CHEMICAL: TALC		OSHA PEL	2.00 MG/CU M		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		
COMMON (I): SILICON DIOXIDE	10%	TLV TWA	0.10 MG/CU M		
		TLV STEL	NOT ESTAB		
CAS: 14808-60-7 CHEMICAL: QUARTZ		OSHA PEL	0.10 MG/CU M		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		
COMMON (NA): EPOXY ADDUCT	20%	TLV TWA	NOT ESTAB		
		TLV STEL	NOT ESTAB		
CAS: 68424-41-9 CHEMICAL: FATTY ACIDS, C18 UNSATD., DIMERS, POLYMERS WITH TRIETHYLENETETRAMINE, REACTION PRODUCTS WITH POLYBISPHENOL A DIGLYCIDYL ETHER		OSHA PEL	NOT ESTAB		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		
COMMON (NA): N-BUTYL ALCOHOL	15%	TLV TWA	50.00 PPM		
		TLV STEL	NOT ESTAB		
CAS: 71-36-3 CHEMICAL: 1-BUTANOL		OSHA PEL	NOT ESTAB		
		CEILING	50.00 (02)		
		RECOMM	NOT ESTAB		
COMMON (NA): TOLUENE	5%	TLV TWA	100.00 PPM		
		TLV STEL	150.00 PPM		
CAS: 108-88-3 CHEMICAL: PHENYL METHYL		OSHA PEL	100.00 PPM		
		CEILING	NOT ESTAB		
		RECOMM	NOT ESTAB		

( 1 ) = THIS MATERIAL IS A CARCINOGEN PER IARC  
( 2 ) = PPM SKIN

\*\*\*\*\* SECTION 3: PHYSICAL DATA \*\*\*\*\*

BOILING POINT: 230 DEG F.  
VAPOR PRESSURE MM HG AT 70 DEG F: 28.0  
VAPOR DENSITY (AIR = 1.0): 5.9  
SPECIFIC GRAVITY: 1.31  
PERCENT VOLATILE BY VOLUME: 49.65

V. A. SPAR CORPORATION  
MATERIAL SAFETY DATA SHEET

18232377  
PAGE 2  
37-00881R

\*\*\*\*\* SECTION 3: PHYSICAL DATA \*\*\*\*\*  
EVAPORATION RATE (QUITY ACETATE 5 II): 2.0  
SOLUBILITY IN WATER: NO  
APPEARANCE AND ODOR: NORMAL FOR A COATINGS PRODUCT.

\*\*\*\*\* SECTION 4: FIRE AND EXPLOSION HAZARD \*\*\*\*\*

FLASH POINT TCC/PH DEG F : 48  
LOWER EXPLOSIVE LIMIT : 1.00  
UPPER EXPLOSIVE LIMIT : 19.00

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES:  
FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.  
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:  
NONE

\*\*\*\*\* SECTION 5: HEALTH HAZARD DATA \*\*\*\*\*

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:  
IMMEDIATE EFFECTS (ACUTE):  
CAN BE ABSORBED THROUGH THE SKIN.  
HAZARFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RESPIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY IRRITATION.  
OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION, CNS DEPRESSION, CORNEAL INJURY/EYE DAMAGE.  
DELAYED EFFECTS (CHRONIC):  
NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHAALING THE CONTENTS MAY BE HARMFUL OR FATAL.  
CONTAINS INGREDIENTS WHICH MAY CAUSE LIVER DAMAGE, KIDNEY DAMAGE, HEARING LOSS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.  
SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.  
CLOTHING: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN CONTAMINATED SHOES.  
INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.  
SWALLOWING: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

\*\*\*\*\* SECTION 6: REACTIVITY DATA \*\*\*\*\*

THIS PRODUCT IS STABLE  
CONDITIONS TO AVOID: NONE  
INCOMPATIBILITY: STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS:  
AMMONIA COMPOUNDS      NITROGEN OXIDES      CARBON DIOXIDE/MONOXIDE

## SARA SECTION 313 CHEMICAL REPORT

DATE: 05/07/89  
CONTROL NO: IB4227852

CUSTOMER: BORN PAINT CO

CUSTOMER NUMBER: 097382000

PRODUCT	PRODUCT NAME	(5) 311/312 CATEGORY	(6) 311/312 TYPE	(3) SECTION 313
089W2K	HB EP THT BSE MED	H-1 H-2 P-3	A	YES

## SUMMARY OF COMPONENTS

CAS NUMBER	CHEMICAL NAME	(7) * PCT * * WT *	(7) * VOLTL *	(8) 311/312 CATEGORY	(3) * SEC * * 313 *	(4) * CAT *	(1) * EXT * * HQ *	(2) * HAZ * * TPQ *
1330-20-7	PHENYL, DIMETHYL	0.6	100%	H-1 P-3	YES			
71-36-3	1-BUTANOL	1.2	100%	H-1 H-2 P-3	YES			
100-41-4	BENZENE, ETHYL	0.3	100%	H-1 H-2 P-3	YES			
111-76-2	ETHANOL, 2-BUTOXY-	2.5	100%	H-1 H-2 P-3	YES			
75-93-3	2-BUTANONE	6.5	100%	H-1 H-2 P-3	YES			

## FOOTNOTES

- (1) = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302  
 (2) = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 307  
 (3) = TOXIC CHEMICAL, SEC. 313  
 (4) = CATEGORY AS REQUIRED BY SEC. 313 (40 CFR 372.42), MUST BE USED ON TOXIC RELEASE INVENTORY FORM  
 (5) = HAZARD CATEGORY FOR SARA SEC. 311/312 REPORTING  
 HEALTH H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD H-2 = DELAYED (CHRONIC) HEALTH HAZARD  
 PHYSICAL P-3 = FIRE HAZARD P-4 = SUDDEN RELEASE OF PRESSURE HAZARD  
 P-5 = REACTIVE HAZARD  
 (6) = TYPE  
 A = LIQUID MIXTURE D = PURE LIQUID  
 B = SOLID MIXTURE E = PURE SOLID  
 C = GASEOUS MIXTURE F = PURE GAS  
 (7) = VOLATILE PERCENT

HAZARDOUS POLYMERIZATION: NONE  
SECTION 8: REACTIVITY DATA  
CONTINUED

SECTION 7: SPILL OR LEAK PROCEDURES

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR ALTMASK FOR LARGE SPILLS IN A CONFINED AREA. ELIMINATE IGNITION SOURCES. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. AVOID ALL PERSONAL CONTACT.

WASTE DISPOSAL METHOD:  
DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

SECTION 8: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:  
WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR. INDS/MSHA APPROVED DURING AND AFTER APPLICATION UNLESS AIR MONITORING VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:  
REQUIRED FOR SPRAYING OR IN A CONFINED AREA. VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF. ELIMINATE IGNITION SOURCES.

PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION.  
EYE PROTECTION: USUAL EYE PROTECTION FOR APPLYING PAINT.  
OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

SECTION 9: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

CONTAINERS SHOULD BE GROUNDED/BONDED WHEN POURING. AVOID FREE FALL OF LIGHT IN EXCESS OF A FEW INCHES.  
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. BASED ON THE PRODUCT FLASH POINT AND VAPOR PRESSURE SUITABLE STORAGE SHOULD BE PROVIDED IN ACCORDANCE WITH OSHA REGULATION 1910.106. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR MELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEARED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;  
TARC - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL - LOWER EXPLOSIVE LIMITS;  
HEL - UPPER EXPLOSIVE LIMITS; MG CB M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS  
MPPDF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH  
ADMINISTRATION; NA-NOT APPLICABLE; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL  
SAFETY AND HEALTH; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;  
Pb-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;  
TCC/PPH-TAG CLOSED CUP/PENSKY-MARTIN; TECH-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.

SECTION 10: DISCLAIMER SECTION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. THE VALSPAR CORPORATION MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. THE VALSPAR CORPORATION FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDORS, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDORS OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.

CUSTOMER NAME : BORN PAINT CO  
 CUSTOMER NUMBER: 097382000  
 CUSTOMER INVOICE : 4227652  
 \*\*\*\*\* SECTION 1: PRODUCT IDENTIFICATION \*\*\*\*\*

MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415  
 MFG TELEPHONE NUMBER : (612) 332-7371  
 24 HR EMERGENCY PHONE NO : 1-800-228-5635  
 CHEMICAL NAME OR FAMILY : PAINT PRODUCT  
 FORMULA : Q89W72K-122-A-06  
 TRADE NAME : 37 89W72K HB EP TNT BSE MED  
 REVISION DATE : 04-03-89

\*\*\*\*\* SECTION 2: HAZARDOUS INGREDIENTS \*\*\*\*\*

NAME	APPROX WT %				
COMMON(NA):ALIPHATIC PETROLEUM DISTILLATES	1%	TLV TWA	NOT ESTAB		
		TLV STEL	NOT ESTAB		
CAS:64742-88-7 CHEMICAL: SOLVENT NAPHTHA (PETRO- LEUM), MEDIUM ALIPHATIC		OSHA PEL	500.00 PPM		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):TALC	15%	TLV TWA	10.00 MG/CU M		
		TLV STEL	NOT ESTAB		
CAS:14807-96-6 CHEMICAL: SILICIC ACID,MAGNESIUM SA LT (1:1)		OSHA PEL	2.00 MG/CU M		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):TITANIUM DIOXIDE	20%	TLV TWA	15.00 MG/CU M		
		TLV STEL	NOT ESTAB		
CAS:13463-87-7 CHEMICAL: TITANIUM OXIDE		OSHA PEL	10.00 MG/CU M		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):SILICA	1%	TLV TWA	10.00 MG/CU M		
		TLV STEL	NOT ESTAB		
CAS:7631-86-9 CHEMICAL: SILICA		OSHA PEL	10.00 MG/CU M		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):EPOXY RESIN	35%	TLV TWA	NOT ESTAB		
		TLV STEL	NOT ESTAB		
CAS:25068-38-0 CHEMICAL: PHENOL, 4,4'-[1-METHYL ETHYLIDENE)BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE		OSHA PEL	NOT ESTAB		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):BUTYL ACETATE	10%	TLV TWA	150.00 PPM		
		TLV STEL	200.00 PPM		
CAS:123-86-4 CHEMICAL: ACETIC ACID, BUTYL ESTER		OSHA PEL	150.00 PPM		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		
COMMON(NA):N-BUTYL ALCOHOL	1%	TLV TWA	50.00 PPM		
		TLV STEL	NOT ESTAB		
CAS:71-36-3 CHEMICAL: 1-BUTANOL		OSHA PEL	NOT ESTAB		
		CEILING	50.00 (01)		
		RECOMMND	NOT ESTAB		
COMMON( 2):BUTYL CELLOSOLVE	5%	TLV TWA	25.00 PPM		
		TLV STEL	NOT ESTAB		
CAS:111-76-2 CHEMICAL: ETHANOL, 2-BUTOXY-		OSHA PEL	25.00 PPM		
		CEILING	NOT ESTAB		
		RECOMMND	NOT ESTAB		

\*\*\*\*\* SECTION 2: HAZARDOUS INGREDIENTS \*\*\*\*\*

COMMON(NA):METHYL ETHYL KETONE 5% TLV TWA 200.00 PPM  
 TLV STEL 300.00 PPM  
 OSHA PEL 200.00 PPM  
 CEILING NOT ESTAB  
 RECOMMND NOT ESTAB

( 1 ) = PPM SKIN  
 ( 2 ) = GLYCOL ETHER, SEE SECTION 5.

\*\*\*\*\* SECTION 3: PHYSICAL DATA \*\*\*\*\*

BOILING POINT: 156 DEG F.  
 VAPOR PRESSURE MM HG AT 68 DEG F: 76.0  
 VAPOR DENSITY (AIR = 1.0): 5.9  
 SPECIFIC GRAVITY: 1.42  
 PERCENT VOLATILE BY VOLUME: 40.12  
 EVAPORATION RATE (BUTYL ACETATE = 1): 5.8  
 SOLUBILITY IN WATER: NO  
 APPEARANCE AND ODOR: NORMAL FOR A COATINGS PRODUCT.

\*\*\*\*\* SECTION 4: FIRE AND EXPLOSION HAZARD \*\*\*\*\*

FLASH POINT TCC/PM DEG F : 49  
 LOWER EXPLOSIVE LIMIT : 1.00  
 UPPER EXPLOSIVE LIMIT : 16.00

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES:  
 FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.  
 CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:  
 NONE

\*\*\*\*\* SECTION 5: HEALTH HAZARD DATA \*\*\*\*\*

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

CAN BE ABSORBED THROUGH THE SKIN.  
 HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RES-  
 PIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY  
 IRRITATION.

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND  
 THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION.

DELAYED EFFECTS (CHRONIC):

CONTAINS GLYCOL ETHER WHICH HAS BEEN SHOWN TO CAUSE BLOOD EFFECTS DAM-  
 AGE IN LABORATORY ANIMALS.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL  
 OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM  
 DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND  
 INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

CONTAINS INGREDIENTS WHICH MAY CAUSE LIVER DAMAGE, KIDNEY DAMAGE,  
 HEARING LOSS, MUCOUS MEMBRANE IRRITATION.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY  
 RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: REMOVE PERSON FROM EXPOSURE AREA. IF BREATHING HAS  
 STOPPED, USE MOUTH-TO-MOUTH RESUSCITATION AND GET MEDICAL ATTENTION.  
 EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES.  
 SKIN CONTACT: WASH WITH SOAP AND WATER.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

CUSTOMER: BORN PAINT CO  
 CUSTOMER NUMBER: 0873B2000

PRODUCT NAME: VC HB EPY CURING AGT H-1 H-2 P-3  
 (6) 311/312  
 CATEGORY TYPE 313  
 SECTION A  
 YES

SUMMARY OF COMPONENTS

CAS NUMBER	CHEMICAL NAME	(17) PCT WT. VOLTL	(5) 311/312 CATEGORY	(3) SEC 313 CAT	(4) EXT HAZ SUB
647-89-7	SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH	2.7	H-1 H-2 P-3	NO	
8030-30-8	NAPHTHA	7.3	H-1 H-2 P-3	NO	
N/A	SALT OF UNSATURATED POLYAMINE AMIDES AND ACIDIDES TENS - SUPPLIER TRADE SECRET	0.1	H-1 H-2 P-3	NO	
90-72-2	PHENOL, 2,4,6-TRIS(DIMETHYLAMINO)METHYL	0.6	H-1	NO	
14807-96-6	TALC	38.7	H-1 H-2	NO	
14808-60-7	QUARTZ	11.4	H-1 H-2	NO	
68424-41-9	FATTY ACIDS, C18 UNSATD. DIMERS, POLYMERS WITH TRI ETHYLENETETRAMINE. REACTION PRODUCTS WITH POLY(BIS PHENOL A DIGLYCIDYL ETHER)	17.5	H-1 H-2 P-3	NO	
71-35-3	1-BUTANOL	16.8	H-1 H-2 P-3	YES	
108-88-3	PHENYL, METHYL	2.9	H-1 H-2 P-3	YES	

FOOTNOTES

- (1) = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- (2) = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- (3) = TOXIC CHEMICAL, SEC. 313
- (4) = CATEGORY AS REQUIRED BY SEC. 313 (40 CFR 372.42) MUST BE USED ON TOXIC RELEASE INVENTORY FORM
- (5) = HAZARD CATEGORY FOR SARA SEC. 311/312 REPORTING  
 H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD  
 H-2 = DELAYED (CHRONIC) HEALTH HAZARD  
 P-3 = FIRE HAZARD  
 P-4 = SUDDEN RELEASE OF PRESSURE HAZARD
- (6) = TYPE  
 A = LIQUID MIXTURE  
 B = SOLID MIXTURE  
 C = GASEOUS MIXTURE  
 D = PURE LIQUID  
 E = PURE SOLID  
 F = PURE GAS
- (7) = VOLATILE PERCENT