

MATERIAL SAFETY DATA SHEET

PAGE 1

REV: 10/88

COMET SUPPLY INC.  
 P.O. BOX 98  
 105 WEST JEFFERSON STREET  
 WASHINGTON IL 61571  
 PHONE: (309) 444-2314

HEALTH - 2  
 FIRE - 4

REACTIVITY - 0  
 EQUIPMENT - --

HAZARD RATINGS: 0 = LEAST 1 = SLIGHT  
 2 = MODERATE 3 = HIGH  
 4 = EXTREME

SECTION I =====PRODUCT DESCRIPTION=====

PRODUCT NAME: COMSQL 130 *Paint Stripper*

SYNONYMS: SOLVENT

CHEMICAL FAMILY: HYDROCARBON MIXTURE

SECTION II =====PRODUCT COMPOSITION=====

INGREDIENT	VOL %	CAS #	TLV
ORINATED SOLVENT	25	75-09-2	100 PPM
ALCOHOL	25	67-63-0	200 PPM
KEYTONE	25	67-64-1	100 PPM
AROMATIC HYDROCARBON	25	108-88-3	100 PPM

SECTION III=====PHYSICAL PROPERTIES=====

BOILING RANGE: 104-235

SPECIFIC GRAVITY (WATER =1) .864

VAPOR PRESSURE AT 20C (MM OF HG) : 75

VAPOR DENSITY (AIR = 1) : 2.7

SOLUBILITY IN WATER: SLIGHT

EVAPORATION RATE: 3.0 APPROX.

% VOLATILES: 75

APPEARANCE AND ODOR: CLEAR, COLORLESS LIQUID.

SECTION IV=====FIRE AND EXPLOSION DATA=====

LOWER FLAMMABILITY LIMITS (% IN AIR) : >1.2

FLASH POINT (AND METHOD) : 60F CDC

FLAMMABILITY CLASSIFICATION: FLAMMABLE

RECOMMENDED EXTINGUISHING MEDIA: NFPA CLASS B EXTINGUISHER (CO2 OR FOAM).

SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE ON FIRE. BUT, IT CAN PROTECT FIRE FIGHTERS AND COOL CLOSED CONTAINERS. USE FOG NOZZLES IF WATER IS USED. USE AIR SUPPLIED BREATHING MASKS.

FIRE/EXPLOSION HAZARDS: KEEP AWAY FROM HEAT AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

SECTION V=====HEALTH INFORMATION=====

THRESHOLD LIMIT VALUE: 100 PPM  
ACUTE TOXICITY:

EFFECTS OF OVEREXPOSURE: IRRITATING RESPIRATORY TRACT. MAY CAUSE DIZZINESS, UNCONSCIOUSNESS OR COMA. MAY ALSO BE IRRITATING TO THE EYES AND SKIN.

EMERGENCY FIRST AID PROCEDURES:

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: FLUSH WITH WATER.

INHALATION: REMOVE TO FRESH AIR. IF DISCOMFORT PERSISTS, GET MEDICAL ATTENTION.

INGESTION: CALL A PHYSICIAN IMMEDIATELY! DO NOT INDUCE VOMITING.

SECTION VI=====REACTIVITY DATA=====

STABILITY: STABLE

CONDITIONS TO AVOID: HEAT, SPARKS AND OPEN FLAME.

INCOMPATIBILITY WITH OTHER MATERIALS: STRONG OXIDIZERS SUCH AS PERMANGANATE.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE FROM INCOMPLETE BURNING.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VII=====SPILL OR LEAK PROCEDURES=====

PROCEDURES IF MATERIAL IS SPILLED OR RELEASED: ISOLATE SPILL. ISOLATE FROM SOURCES OF IGNITION. MOP OR SWEEP UP AND CONTAINERIZE.

WASTE DISPOSAL PROCEDURES: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL POLLUTION REGULATIONS.

## SECTION VIII=====SPECIAL PROTECTION INFORMATION=====

RESPIRATORY PROTECTION: AS REQUIRED TO KEEP ENVIRONMENT BELOW TLV.

LOCAL EXHAUST: PREFERABLE.

PROTECTIVE GLOVES: MUST NOT DISSOLVE IN SOLVENTS.

EYE PROTECTION: SAFETY GOGGLES.

## SECTION IX=====ADDITIONAL PRECAUTIONS=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: HARMFUL IF SWALLOWED!  
EXTREMELY FLAMMABLE! KEEP AWAY FROM HEAT AND OPEN FLAME. USE ONLY WITH  
ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. KEEP  
CONTAINER CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS: STORE LARGE AMOUNTS IN STRUCTURES MADE FOR FLAMMABLE  
LIQUIDS. EMPTY CONTAINER HAZARDOUS. CONTINUE ALL LABEL PRECAUTIONS.

THE INFORMATION HEREIN IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE  
CORRECT AS OF THE DATE HEREOF. HOWEVER COMET MAKES NO REPRESENTATION AS  
TO THE COMPLETENESS AND ACCURACY THEREOF. USERS MUST MAKE THEIR OWN  
DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PURPOSES  
PRIOR TO USE.

COMET SUPPLY, INC. ACCEPTS NO RESPONSIBILITY FOR CHANGES IN THE  
CHARACTERISTICS OF THIS PRODUCT AS A RESULT OF ITS USE. THE USER MUST  
DETERMINE WHAT CHANGES OCCUR AND THE RELEVANCE OF THESE CHANGES TO THE HEALTH  
AND SAFETY OF INDIVIDUALS AND THE ENVIRONMENT.