

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004



Material Safety Data Sheet

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol)
MANUFACTURER: 3M
DIVISION: Industrial Adhesives and Tapes
 Sumitomo/3M Ltd.
ADDRESS: 3M Center
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/29/2004
Supersedes Date: 07/31/2003

Document Group: 16-3472-4

Product Use:

Intended Use: general purpose aerosol adhesive
Specific Use: General Purpose Aerosol adhesive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
ACETONE	67-64-1	20 - 30
NON-VOLATILE COMPONENTS - N.J. TRADE SECRET REGISTRY NO. 04499600-6433P	Trade Secret	20 - 30
PROPANE	74-98-6	15 - 25
2-METHYLPENTANE	107-83-5	10 - 20
CYCLOHEXANE	110-82-7	3 - 7
3-METHYLPENTANE	96-14-0	3 - 7
2,2-DIMETHYLBUTANE	75-83-2	1 - 3
2,3-DIMETHYLBUTANE	79-29-8	1 - 3
HEXANE	110-54-3	<0.8

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Aerosol
Odor, Color, Grade: clear, sweet fruity odor
General Physical Form: Gas aerosol

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Aerosol container contains flammable material under pressure. Aerosol container contains flammable gas under pressure. Flammable liquefied gas. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Prolonged or repeated exposure may cause:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

May be absorbed through skin and cause target organ effects.

Inhalation:

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Intentional concentration and inhalation may be harmful or fatal.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure, above recommended guidelines, may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Kidney Effects: Signs/symptoms may include reduced or absent urine production, increased serum creatinine, lower back pain, increased protein in urine, and increased blood urea nitrogen (BUN).

SECTION 4: FIRST AID MEASURES

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	<i>No Data Available</i>
Flash Point	-42.00 °F [Test Method: Tagliabue Closed Cup]
Flammable Limits - LEL	<i>No Data Available</i>
Flammable Limits - UEL	<i>No Data Available</i>
OSHA Flammability Classification:	Class IA Flammable Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Closed containers exposed to heat from fire may build pressure and explode. Aerosol container contains flammable material under pressure. Flammable liquefied gas.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate organic solvent. Read and follow

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Aerosol container contains flammable gas under pressure. No smoking while handling this material. Do not spray near flames or sources of ignition. Do not pierce or burn container, even after use. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Keep out of the reach of children.

7.2 STORAGE

Store away from heat. Store away from acids. Store out of direct sunlight.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with functioning spray booth or local exhaust. Use with appropriate local exhaust ventilation. Do not use in a confined area or areas with little or no air movement. Use in a well-ventilated area. If exhaust ventilation is not available, use appropriate respiratory protection. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment. Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields.

8.2.2 Skin Protection

Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

8.2.3 Respiratory Protection

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ACETONE	ACGIH	TWA	500 ppm	Table A4
ACETONE	ACGIH	STEL	750 ppm	Table A4
ACETONE	OSHA	TWA, Vacated	750 ppm	
ACETONE	OSHA	TWA	1000 ppm	Table Z-1
ACETONE	OSHA	STEL, Vacated	1000 ppm	
CYCLOHEXANE	ACGIH	TWA	100 ppm	
CYCLOHEXANE	OSHA	TWA	300 ppm	Table Z-1
HEXANE	ACGIH	TWA	50 ppm	Skin Notation*

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

HEXANE	OSHA	TWA, Vacated	50 ppm	Table Z-1A
HEXANE	OSHA	TWA	500 ppm	Table Z-1A
HEXANE (ISOMERS OTHER THAN N-HEXANE)	ACGIH	TWA	500 ppm	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	ACGIH	STEL	1000 ppm	
PROPANE	ACGIH	TWA	2500 ppm	
PROPANE	OSHA	TWA	1000 ppm	Table Z-1

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Guideline
- OSHA: Occupational Safety and Health Administration
- AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Aerosol
Odor, Color, Grade:	clear, sweet fruity odor
General Physical Form:	Gas aerosol
Autoignition temperature	<i>No Data Available</i>
Flash Point	-42.00 °F [<i>Test Method: Tagliabue Closed Cup</i>]
Flammable Limits - LEL	<i>No Data Available</i>
Flammable Limits - UEL	<i>No Data Available</i>
Boiling point	<i>Not Applicable</i>
Vapor Density	2.97 [<i>Ref Std: AIR=1</i>]
Specific Gravity	0.726 [<i>Ref Std: WATER=1</i>]
Freezing point	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Nil
Vaporization rate	1.90 [<i>Ref Std: ETHER=1</i>]
Hazardous Air Pollutants	0.4 % weight [<i>Test Method: Calculated</i>]
Hazardous Air Pollutants	0.016 lb HAPS/lb solids
Hazardous Air Pollutants	0.02 lb HAPS/gal [<i>Test Method: Calculated</i>]
Stable Organic Compounds	Approximately 51 % [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Percent volatile	<=75 % weight
Flash Point: Less H2O & Exempt Solvents	468 g/l
Boiling point	<i>Not Applicable</i>

SECTION 10: STABILITY AND REACTIVITY

Stable.

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

Materials and Conditions to Avoid: Heat

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate uncured product in a permitted hazardous waste incinerator. Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Facility must be capable of handling aerosol cans. The facility should be equipped to handle gaseous waste.

Dispose of empty product containers in a sanitary landfill.

RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

62-4977-0926-1, 62-4977-0927-9, 62-4977-0928-7, 62-4977-0929-5, 62-4977-0939-4, 62-4977-2924-4, 62-4977-2926-9, 62-4977-2928-5, 62-4977-2929-3, 62-4977-4026-6, 62-4977-4030-8, 62-4977-4830-1, 62-4977-4835-0, 62-4977-4840-0, 62-4977-4845-9, 62-4977-4925-9, 62-4977-4926-7, 62-4977-4927-5, 62-4977-4928-3, 62-4977-4930-9, 62-4977-4931-7, 62-4977-4932-5, 62-4977-4933-3, 62-4977-4935-8, 62-4977-4937-4, 62-4977-4938-2, 62-4977-4939-0

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
CYCLOHEXANE	110-82-7	3 - 7

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
HEXANE	110-54-3	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
CYCLOHEXANE	110-82-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
ACETONE	67-64-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

This material contains one or more ingredients that may be regulated by the International Traffic in Arms Regulation (ITAR), an

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

export control of US military technology and chemicals. Prior to export of this material or any product containing this material, determine whether a proper license from the Department of State must be obtained. See 22CFR 120-130 for any specific requirements.

Non hazardous according to WHMIS criteria.

Contact 3M for more information.

WHMIS: Non-hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 4 **Reactivity:** 0 **Special Hazards:** None
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 **Flammability:** 4 **Reactivity:** 0 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 16: NFPA hazard classification heading was modified.

Section 16: HMIS hazard classification heading was modified.

Section 3: Other potential health effects heading was modified.

Copyright was modified.

Section 8: Exposure guidelines data source legend was modified.

Section 5: Fire fighting procedures information was modified.

Section 15: 311/312 hazard categories heading was modified.

Section 15: International regulations information was modified.

Section 15: State regulations information was modified.

Section 15: US federal regulations information was modified.

Section 15: WHMIS regulations information was modified.

Section 10: Hazardous polymerization heading was modified.

Section 15: TSCA section 12[b] text was modified.

Section 3: Other health effects information was modified.

Section 14: ID Number(s) was modified.

Section 16: HMIS explanation was modified.

Section 16: NFPA explanation was modified.

Section 15: Inventories information was modified.

3M MATERIAL SAFETY DATA SHEET 3M(TM) Super 77(TM) Multipurpose Adhesive (Aerosol) 03/29/2004

Section 15: EPCRA 313 text was modified.

Section 12: Ecotoxicological information heading was modified.

Section 12: Chemical fate information heading was modified.

Section 8: Exposure guidelines legend was modified.

Section 8: Exposure guideline note was modified.

Section 16: NFPA hazard classification for special hazards was modified.

Section 16: NFPA hazard classification for aerosol storage was modified.

Section 12: Ecotoxicological phrase was modified.

Section 12: Chemical Fate phrase was modified.

Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.