

The Armor All/STP Products Company

1221 Broadway Oakland, CA 94612 Tel. (510) 271-7000

Material Safety Data Sheet

I Product: STP® OIL TREATMENT Description: DARK BROWN LIQUID WITH A HYDROCARBON ODOR Emergency Telephone Nos. Other Designations Distributor For medical emergencies call: The Armor All/STP Products (800) 446-1014 For Transportation Emergencies call: Oil Additive Company (800) 424-9300 (Chemtrec) 1221 Broadway Oakland, CA 94612 II Health Hazard Data III Hazardous Ingredients Eye Irritant. Prolonged skin contact may cause irritation or dermatitis. Vapors Worker Exposure Limit 5 mg/ m³ TWA PEL/TLV TWA Concentration Ingredients or mists may cause respiratory irritation. Swallowing may cause irritation. Mineral Oil 60-100% nausea, vomiting and diarrhea. Aspiration from ingestion may cause lipid CAS# Mixture pneumonia. Petroleum Distillates 10-30% 500 ppm TLV-TWA Individuals with preexisting skin disorders may be at increased risk from CAS# Mixture exposure to this product. 1-5% None established Zinc Compounds Under normal consumer use and conditions, the likelihood of adverse health CAS# Proprietary effects is low. TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average. FIRST AID: PEL = Permissible Exposure Limit EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get immediate medical attention. None of the ingredients in this product are on the IARC, NTP or OSHA SKIN CONTACT: Remove contaminated clothing. Wash contact area with carcinogen list. soap and water. If irritation persists, get medical attention. INGESTION: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical attention by calling a poison Control or doctor. Never give anything by mouth to an unconscious or drowsy person. INHALATION: If symptoms develop, remove to fresh air. If breathing becomes difficult, give oxygen or administer artificial respiration. Get medical attention if symptoms appear. V Transportation and Regulatory Data IV Special Protection and Precautions Hyglenic Practices: Wash hands thoroughly after contact. DOT/IMO/IATA: Not Restricted Engineering Controls: Use local and/or general ventilation to minimize TSCA Status: All ingredients in this product are listed on the TSCA inventory. exposure to vapor-or mists. EPA - SARA Title III/CERCLA: Personal Protective Equipment: Wear safety glasses with sideshields. Wear This product is regulated under Sections 311/312. This product contains Zinc neoprene or nitrile gloves to prevent skin contact. Use a NIOSH-approved compounds (1-5%), which are regulated under Sara 313 and Section respirator if exposure exceeds occupational limits. 304/CERCLA Keep container closed when not in use. KEEP OUT OF REACH OF CHILDREN VI Spill Procedures/Waste Disposal VII Reactivity Data Spill Procedures: Wear appropriate protective equipment. Collect with Stability: Stable suitable absorbent material and place into a container for disposal. Prevent Hazardous Polymerization: Will not occur. product from entering sewer or waterways by diking or impounding. Notify Hazardous Decomposition: Carbon monoxide, carbon dioxide and hydrogen National Response Center if spill of any amount enters navigable waters, sulfide. contiguous zones or adjoining shorelines. Report spills as required under Incompatibilities: Strong oxidizing agents. federal, state and local regulations. Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations. VIII Fire and Explosion Data IX Physical Data Flash Point: 275°F (CC) Specific Gravity . Fire Extinguishing Agents: Foam, carbon dioxide, dry chemical or water spray Solubility in Water..... Viscosity250 cSt@ 100°C (fog). Cool fire exposed containers with water. Products of Combustion: Carbon monoxide, carbon dioxide and hydrogen

@1963, 1991 THE CLOROX COMPANY

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

DATE PREPARED 4/03

sulfide.