

MATERIAL SAFETY DATA SHEET

1010-
07 00

MANUFACTURER'S NAME
THE THOMPSON'S COMPANY
10136 Magnolia Drive
Olive Branch, MS 38654

EMERGENCY TELEPHONE NO.
(216) 566-2917

DATE OF PREPARATION
28-MAR-00

INFORMATION TELEPHONE NO.
(216) 566-2902

 =====
 Section I -- PRODUCT IDENTIFICATION
 =====

PRODUCT NUMBER	HMIS CODES
1010-	Health 3 Flammability 2 Reactivity 0

PRODUCT NAME
WATER SEAL* Waterproofofer
PRODUCT CLASS
Sealer

 =====
 Section II -- HAZARDOUS INGREDIENTS
 =====

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Med. Aliphatic Hydrocarbon Solvent 64742-88-7	61	Not Established			2.00
Mineral Spirits. 64742-88-7	5	100	100	PPM	2.00
Paraffin Oil 8012-95-1	14	5	5 MG/M3 as M		0.00
Light Aromatic Hydrocarbons. 64742-95-6	1	Not Established			3.80
1,3,5-Trimethylbenzene 108-67-8	1	25	25	PPM	10.00
1,2,4-Trimethylbenzene 95-63-6	2	25	25	PPM	2.03

 =====
 Section III -- PHYSICAL DATA
 =====

PRODUCT WEIGHT	6.79 lb/gal	813 g/l
SPECIFIC GRAVITY	0.82	
BOILING POINT	300 - 425 F	148 - 218 C
MELTING POINT	Not Available	
VOLATILE VOLUME	73 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
4.79 lb/gal	575 g/l	Less Federally Exempt Solvents
4.79 lb/gal	575 g/l	Emitted VOC

Continued on page 2

=====
Section VI -- REACTIVITY DATA

STABILITY -- Stable
CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur
=====

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.
=====

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), 3 mg./m³ (respirable fraction), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

=====
Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY

2

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are COMBUSTIBLE. Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====
Section X -- OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
95-63-6	1,2,4-Trimethylbenzene	2	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.