

## MATERIAL SAFETY DATA SHEET

B60VZ70  
02 00

## Section 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER	B60VZ70	HMIS CODES	
		Health	2*
		Flammability	3
		Reactivity	0
PRODUCT NAME	TILECLAD*High Solids Enamel (Part B), Hardener		
MANUFACTURER'S NAME	THE SHERWIN WILLIAMS COMPANY	EMERGENCY TELEPHONE NO.	(216) 5662917
	101 Prospect Avenue N.W.		
	Cleveland, OH 44115		
DATE OF PREPARATION	26OCT05	INFORMATION TELEPHONE NO.	(216) 5662902

## Section 2 COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
3	100414	Ethylbenzene		
		ACGIH TLV	100 ppm	7.1 mm
		ACGIH TLV	125 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	125 ppm STEL	
19	1330207	Xylene		
		ACGIH TLV	100 ppm	5.9 mm
		ACGIH TLV	150 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	150 ppm STEL	
3	64742956	Light Aromatic Hydrocarbons		
		ACGIH TLV	Not Available	3.8 mm
		OSHA PEL	Not Available	
4	108678	1,3,5-Trimethylbenzene		
		ACGIH TLV	25 ppm	2 mm
		OSHA PEL	25 ppm	
5	95636	1,2,4-Trimethylbenzene		
		ACGIH TLV	25 ppm	2.03 mm
		OSHA PEL	25 ppm	
65		Proprietary Epoxy Polymer		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	

## Section 3 HAZARD IDENTIFICATION

## ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

B60VZ70

page 2

## =====

## EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic skin reaction in susceptible persons or skin sensitization

## CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

## =====

## Section 4 FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.SKIN: Wash affected area thoroughly with soap and water.  
If irritation persists or occurs later, get medical attention.Remove contaminated clothing and launder before reuse.  
INHALATION: If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.INGESTION: Do not induce vomiting.  
Get medical attention immediately.

## =====

## Section 5 FIRE FIGHTING MEASURES

FLASH POINT LEL UEL  
82 F PMCC 0.7 7.0

## FLAMMABILITY CLASSIFICATION

RED LABEL Flammable, Flash below 100 F

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat.

B60VZ70

page 3

## Section 6 ACCIDENTAL RELEASE MEASURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.  
Remove with inert absorbent.

## Section 7 HANDLING AND STORAGE

## STORAGE CATEGORY

DOL Storage Class IC

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are FLAMMABLE. Keep away from heat, sparks, and open flame.  
During use and until all vapors are gone: Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights, and heaters. Turn off stoves, electric tools and appliances, and any other sources of ignition.  
Consult NFPA Code. Use approved Bonding and Grounding procedures.  
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## Section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.  
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.  
Wash hands after using.  
This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

## EYE PROTECTION

Wear safety spectacles with unperforated side shields.

## OTHER PROTECTIVE EQUIPMENT

Use of barrier cream on exposed skin is recommended.

## OTHER PRECAUTIONS

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the

B60VZ70

page 4

 =====  
 Section 9 PHYSICAL AND CHEMICAL PROPERTIES
 =====

PRODUCT WEIGHT	8.75 lb/gal	1048 g/l
SPECIFIC GRAVITY	1.05	
BOILING POINT	277 360 F	136 182 C
MELTING POINT	Not Available	
VOLATILE VOLUME	42 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
3.06 lb/gal	366 g/l	Less Water and Federally Exempt Solvents
3.06 lb/gal	366 g/l	Emitted VOC

 =====  
 Section 10 STABILITY AND REACTIVITY
 =====

STABILITY Stable  
 CONDITIONS TO AVOID  
 None known.  
 INCOMPATIBILITIES  
 None known.  
 HAZARDOUS DECOMPOSITION PRODUCTS  
 By fire: Carbon Dioxide, Carbon Monoxide  
 HAZARDOUS POLYMERIZATION  
 Will not occur

 =====  
 Section 11 TOXICOLOGICAL INFORMATION
 =====

## CHRONIC HEALTH HAZARDS

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations.

B60VZ70

page 5

CAS No.	Ingredient Name				
100414	Ethylbenzene	LC50	RAT	4HR	Not Available
		LD50	RAT		3500 mg/kg
1330207	Xylene	LC50	RAT	4HR	5000 ppm
		LD50	RAT		4300 mg/kg
64742956	Light Aromatic Hydrocarbons	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
108678	1,3,5-Trimethylbenzene	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
95636	1,2,4-Trimethylbenzene	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
Proprietary	Epoxy Polymer	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

## Section 12 ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

No data available.

## Section 13 DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial and Local regulations regarding pollution.

## Section 14 TRANSPORT INFORMATION

No data available.

## Section 15 REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOND	% by WT	% Element
100414	Ethylbenzene	3	
1330207	Xylene	19	
95636	1,2,4-Trimethylbenzene	5	

B60VZ70

page 6

## =====

CALIFORNIA PROPOSITION 65  
WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.  
TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## =====

## Section 16 OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.