

Safety Data Sheet

312828 - 641

Page 1 of 7

MSDS-No.: 153498

Date of issue: 25.05.2015

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:

312828 - 641

Intended use:

Adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone:

+61 (3) 9724 6444

Emergency information:

24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class

Hazard Category

Category 3

Serious eye irritation

Target Organ Systemic Toxicant -

Single exposure

Chronic hazards to the aquatic

environment

Category 2A

Category 3

Target organ

respiratory tract irritation

Hazard pictogram:

Signal word:

Warning

MSDS-No.: 153498 V001.2

312828 - 641

Hazard statement(s):

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response:

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Classification of material Xi - Irritant

Risk phrases:

R36/37 Irritating to eyes and respiratory system.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.

S25 Avoid contact with eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

HAZARDOUS

Section 3. Composition / information on ingredients

General chemical description:

Mixture

Type of preparation:

Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Polyethylene glycol 200 dimethacrylate	25852-47-5	60- 100 %
Cumene hydroperoxide	80-15-9	< 3 %
non hazardous ingredients~		10- 30 %

V001.2

312828 - 641

Section 4. First aid measures

Ingestion:

Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin:

In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water.

In case of adverse health effects seek medical advice.

Eyes:

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

Inhalation:

Move to fresh air.

Keep warm and in a quiet place.

Seek medical advice.

First Aid facilities:

Eye wash and safety shower Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically and supportively.

Section 5. Fire fighting measures

Suitable extinguishing media:

Foam, dry chemical or carbon dioxide.

Decomposition products in case of fire::

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide.

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice:

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Ensure adequate ventilation.

Wear appropriate personal protective equipment.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

V001.2

312828 - 641

Section 8. Exposure controls / personal protection

National exposure standards:

None

Engineering controls:

Ensure adequate ventilation.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing. Suitable protective gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:

yellow Liquid

Odor:

characteristic

Specific gravity:

1.08 > 149.0 °C (> 300.2 °F)

Boiling point: Flash point:

> 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Vapor pressure:

< 5 mm hg

(; 27 °C (80.6 °F))

1.08 g/cm3

Density: VOC content:

10.4 % 112 g/l

Section 10. Stability and reactivity

Stability:

Stable under recommended storage conditions.

Conditions to avoid:

Heat, flames, sparks and other sources of ignition.

Extremes of temperature.

Incompatible materials:

Strong oxidizing agents.

Reducing agents.

Keep away from alkalis.

Metal oxides. Reacts with acids.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide.

Hazardous polymerization:

Will not occur.

Section 11. Toxicological information

V001.2

312828 - 641

Health Effects:

Ingestion:

May cause irritation to the gastrointestinal tract, mouth and mucous membranes.

Skin:

May cause mild skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Causes serious eye irritation. Eyes:

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. This product is irritating to the respiratory system.

Inhalation:

Inhalation of vapors may cause moderate to severe respiratory tract irritation.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Polyethylene glycol 200 dimethacrylate 25852-47-5	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 423 (Acute Oral toxicity)
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	

Section 12. Ecological information

V001.2

312828 - 641

General ecological information:

Do not empty into drains, soil or bodies of water.

Ecotoxicity:

Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Polyethylene glycol 200	LC50	> 100 mg/1	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute
dimethacrylate 25852-47-5 Cumene hydroperoxide 80-15-9 Cumene hydroperoxide 80-15-9	LC50 EC50	3.9 mg/l	Fish Daphnia	96 h 48 h	Oncorhynchus mykiss Daphnia magna	Toxicity Test) OECD Guideline 203 (Fish, Acute Toxicity Test) OECD Guideline 202 (Daphnia sp.
Cumene hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Acute Immobilisation Test) OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					

Section 13. Disposal considerations

Waste disposal of product:

Dispose of in accordance with local and national regulations.

Disposal for uncleaned package:

Disposal of empty packaging at suitable material collection for recycling.

After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

V001.2

312828 - 641

Section 15. Regulatory information

SUSMP Poisons Schedule

None

AICS:

All components are listed or are exempt from listing on the Australian Inventory of Chemical Substances (AICS).

Section 16. Other information

Abbreviations/acronyms:

ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue:

Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Other information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Date of previous issue:

24.09.2010

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been.developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.