

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200), Health Canada HPR (SOR/2015-17), and Mexico NOM-018-STPS-2015

## SECTION 1: Identification

**Product Identifier** John Deere Turf-Gard® Supreme Motor Oil  
**Other means of identification Code** John Deere Turf-Gard® Supreme Motor Oil, SAE 10W-30  
**776105**  
**Issue date** 19-Nov-2019  
**Relevant identified uses** Automotive Engine Oil  
**Uses advised against** All others  
**24 Hour Emergency Phone Number** CHEMTREC: 1-800-424-9300  
CHEMTREC Mexico 01-800-681-9531  
CHEMTREC Global +1 703 527 3887  
**Manufacturer/Supplier** Phillips 66 Lubricants  
A Division of Phillips 66 Company  
P.O. Box 421959  
Houston, Texas 77242-1959  
**SDS Information** URL: www.phillips66.com/SDS  
Phone: 800-762-0942  
Email: SDS@P66.com  
**Customer Service** U.S.: 800-368-7128 or International: 1-832-765-2500  
**Technical Information** 1-877-445-9198

## SECTION 2: Hazard identification

**Classified Hazards** No classified hazards  
**Hazards Not Otherwise Classified (HNOC)**  
PHNOC: None known  
HHNOC: None known

### Label elements

No classified hazards

## SECTION 3: Composition/information on ingredients

Chemical Name	CASRN	Concentration <sup>1</sup>
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	<100

<sup>1</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First aid measures

**Eye Contact:** If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

**Skin Contact:** First aid is not normally required. However, it is good practice to wash any chemical from the skin.

**Inhalation:** First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.

**Ingestion:** First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

**Most important symptoms and effects, both acute and delayed:** Inhalation of oil mists or vapors generated at elevated temperatures may cause respiratory irritation. Accidental ingestion can result in minor irritation of the digestive tract, nausea and diarrhea. Prolonged or repeated contact may dry skin and cause irritation.

**Notes to Physician:** Acute aspirations of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

## SECTION 5: Firefighting measures

### NFPA 704: National Fire Protection Association

Health 0                      Flammability: 1                      Instability: 0



0 = minimal hazard  
1 = slight hazard  
2 = moderate hazard  
3 = severe hazard  
4 = extreme hazard

**Extinguishing Media:** Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F / 100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### Specific hazards arising from the chemical

**Unusual Fire & Explosion Hazards:** This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

**Special protective actions for fire-fighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

## SECTION 6: Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

**Environmental Precautions:** Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

**Methods and material for containment and cleaning up:** Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or

disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate disposal.

## SECTION 7: Handling and storage

**Precautions for safe handling:** Keep away from flames and hot surfaces. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Spills will produce very slippery surfaces. Used motor oils have been shown to cause skin cancer in mice after repeated application to the skin without washing. Brief or intermittent skin contact with used motor oil is not expected to cause harm if the oil is thoroughly removed by washing with soap and water. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Do not wear contaminated clothing or shoes.

**Conditions for safe storage:** Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated area away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

## SECTION 8: Exposure controls/personal protection

Occupational exposure limits				
Chemical Name	ACGIH	OSHA	Mexico	Phillips 66
Distillates, petroleum, hydrotreated heavy paraffinic	TWA-8hr: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if Generated	---	---	---

State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

### Biological occupational exposure limits

None.

**Engineering controls:** If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:** The use of eye/face protection is not normally required; however, good industrial hygiene practice suggests the use of eye protection that meets or exceeds ANSI Z.87.1 whenever working with chemicals.

**Skin/Hand Protection:** The use of skin protection is not normally required; however, good industrial hygiene practice suggests the use of gloves or other appropriate skin protection whenever working with chemicals. Suggested protective materials: Nitrile rubber

**Respiratory Protection:** Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with R or P95 filters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

**Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.**

## SECTION 9: Physical and chemical properties

**Note:** Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

<b>Appearance:</b> Amber, Transparent	<b>Flash Point:</b> Minimum 365 °F / 185 °C
<b>Physical Form:</b> Liquid	<b>Test Method:</b> Pensky-Martens Closed Cup (PMCC), ASTM D93, EPA 1010
<b>Odor:</b> Petroleum	<b>Initial Boiling Point/Range:</b> No data
<b>Odor Threshold:</b> No data	<b>Vapor Pressure:</b> <1 mm Hg
<b>pH:</b> Not applicable	<b>Partition Coefficient (n-octanol/water) (Kow):</b> No data
<b>Vapor Density (air=1):</b> >1	<b>Melting/Freezing Point:</b> No data
<b>Upper Explosive Limits (vol % in air):</b> No data	<b>Auto-ignition Temperature:</b> No data
<b>Lower Explosive Limits (vol % in air):</b> No data	<b>Decomposition Temperature:</b> No data
<b>Evaporation Rate (nBuAc=1):</b> <1	<b>Specific Gravity (water=1):</b> 0.86 - 0.87 @ 60°F (15.6°C)
<b>Particle Size:</b> Not applicable	<b>Bulk Density:</b> 7.16 - 7.24 lbs/gal
<b>Percent Volatile:</b> Negligible	<b>Viscosity:</b> 10.0 - 11.0 cSt @ 100°C; 64.0 - 72.0 cSt @ 40°C
<b>Flammability (solid, gas):</b> Not applicable	<b>Pour Point:</b> No data
<b>Solubility in Water:</b> Negligible	

## SECTION 10: Stability and reactivity

**Reactivity:** Not chemically reactive.

**Chemical stability:** Stable under normal ambient and anticipated conditions of use.

**Possibility of hazardous reactions:** Hazardous reactions not anticipated.

**Conditions to avoid:** Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.

**Incompatible materials:** Avoid contact with strong oxidizing agents and strong reducing agents.

**Hazardous decomposition products:** Not anticipated under normal conditions of use. During use in engines, contamination of oil with low levels of hazardous fuel combustion by-products (e.g. polycyclic aromatic hydrocarbons) may occur.

## SECTION 11: Toxicological information

### Information on Toxicological Effects

#### Substance / Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful		>5 mg/L (mist, estimated)
Dermal	Unlikely to be harmful		> 2 g/kg (estimated)
Oral	Unlikely to be harmful		> 5 g/kg (estimated)

**Likely Routes of Exposure:** Inhalation, eye contact, skin contact

**Aspiration Hazard:** Not expected to be an aspiration hazard

**Skin Corrosion/Irritation:** Not expected to be irritating. Repeated exposure may cause skin dryness or cracking.

**Serious Eye Damage/Irritation:** Not expected to be irritating.

**Skin Sensitization:** No information available on the mixture, however none of the components have been classified for skin sensitization (or are below the concentration threshold for classification).

**Respiratory Sensitization:** No information available.

**Specific Target Organ Toxicity (Single Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Repeated Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Carcinogenicity:** No information available on the mixture, however none of the components have been classified for carcinogenicity (or are below the concentration threshold for classification).

**Germ Cell Mutagenicity:** No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification).

**Reproductive Toxicity:** No information available on the mixture, however none of the components have been classified for reproductive toxicity (or are below the concentration threshold for classification).

#### Information on Toxicological Effects of Components

##### Distillates, petroleum, hydrotreated heavy paraffinic

**Carcinogenicity:** This oil has been highly refined by a variety of processes to reduce aromatics and improve performance characteristics. It meets the IP-346 criteria of less than 3 percent PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.

## SECTION 12: Ecological information

### **GHS Classification:** **No classified hazards**

**Toxicity:** All acute aquatic toxicity studies on samples of lubricant base oils show acute toxicity values greater than 100 mg/L for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions.

**Persistence and Degradability:** The hydrocarbons in this material are not readily biodegradable, but since they can be degraded by microorganisms, they are regarded as inherently biodegradable.

**Bioaccumulative Potential:** Log Kow values measured for the hydrocarbon components of this material are greater than 5.3, and therefore regarded as having the potential to bioaccumulate. In practice, metabolic processes may reduce bioconcentration.

**Mobility in Soil:** Volatilization to air is not expected to be a significant fate process due to the low vapor pressure of this material. In water, base oils will float and spread over the surface at a rate dependent upon viscosity. There will be significant removal of hydrocarbons from the water by sediment adsorption. In soil and sediment, hydrocarbon components will show low mobility with adsorption to sediments being the predominant physical process. The main fate process is expected to be slow biodegradation of the hydrocarbon constituents in soil and sediment.

**Other adverse effects:** None anticipated.

## SECTION 13: Disposal considerations

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations. This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste and is not believed to exhibit characteristics of hazardous waste. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the SDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste. This material under most intended uses would become "Used Oil" due to contamination by physical or chemical impurities. Whenever possible, Recycle used oil in accordance with applicable federal and state or local regulations. Container contents should be completely used and containers should be emptied prior to discard.

## SECTION 14: Transport information

**UN Number:** Not regulated  
**UN proper shipping name:** None  
**Transport hazard class(es):** None  
**Packing Group:** None  
**Environmental Hazard(s):** This product does not meet the DOT/UN/IMDG/IMO criteria of a marine pollutant  
**Special precautions for user:** If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil)  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable

## SECTION 15: Regulatory information

### **CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds)**

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

### **CERCLA/SARA - Section 311/312 (Title III Hazard Categories)**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

### **CERCLA/SARA - Section 313 and 40 CFR 372**

This material does not contain any chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372.

### **EPA (CERCLA) Reportable Quantity (in pounds)**

This material does not contain any chemicals with CERCLA Reportable Quantities.

### **California Proposition 65**

This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

### **International Inventories**

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.  
All components are either on the DSL, or are exempt from DSL listing requirements.

## SECTION 16: Other information

Issue date	Previous Issue Date:	SDS Number	Status:
19-Nov-2019	08-Jan-2014	776105	FINAL

### **Revised Sections or Basis for Revision:**

Periodic review and update

### **Mexican NOM-018-STPS-2015:**

The information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

### **Guide to Abbreviations:**

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; HPR = Hazardous Products Regulations; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

### **Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to

adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.



# SAFETY DATA SHEET

Issuing Date 20-Jul-2017

Revision Date 20-Jul-2017

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION

### Product identifier

**Product Name** LEAD ACID BATTERY WET FILLED WITH ACID

### Other means of identification

**Product Code(s)** 1110599

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lead acid battery

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

**Supplier Identification** East Penn Mfg.

**Address**  
Deka Rd  
Lyon Station  
PA  
19536  
US

**Telephone**  
Phone:610-682-6361  
Fax:610-682-1650

**E-mail** mgriffith@dekabatteries.com

### Emergency telephone number

**Company Emergency Phone Number** 610-682-6361

## 2. HAZARDS IDENTIFICATION

### Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Skin corrosion/irritation	Category 1





Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1A
Effects on or via lactation	Yes
Specific target organ toxicity (repeated exposure)	Category 1
Corrosive to metals	Category 1

This is a battery. In case of rupture: the above hazards exist.

**Appearance** Varies

**Physical state** Solid

**Odor** Odorless

**GHS Label elements, including precautionary statements**

**Danger**

**Hazard statements**

- Harmful if swallowed
- Toxic if inhaled
- Causes severe skin burns and eye damage
- May cause cancer
- May damage fertility or the unborn child
- May cause harm to breast-fed children
- Causes damage to organs through prolonged or repeated exposure
- May be corrosive to metals



**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Do not breathe dust/fume/gas/mist/vapors/spray
- Avoid contact during pregnancy/while nursing
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Keep only in original container

**Precautionary Statements - Response**

- Immediately call a POISON CENTER or doctor/physician
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician

**Skin**

- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse

**Inhalation**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell

Immediately call a POISON CENTER or doctor/physician

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

**Spill**

Absorb spillage to prevent material damage

**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store in corrosion resistant container with a resistant inner liner

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

Very toxic to aquatic life with long lasting effects.

**Unknown acute toxicity** 100 % of the mixture consists of ingredient(s) of unknown toxicity

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

26 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

26 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable.

**Mixture**

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lead	7439-92-1	70	-	-
Sulfuric acid	7664-93-9	26	-	-
Antimony	7440-36-0	4	-	-

**4. FIRST AID MEASURES**

**First aid measures**

**General advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery.

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Do not breathe dust. Get immediate medical advice/attention.



<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Specific hazards arising from the chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Hazardous Combustion Products</b>	Carbon oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.
<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Attention! Corrosive material. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not



breathe dust.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes. Do not breathe dust. Avoid generation of dust.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep out of the reach of children. Store away from other materials. Store locked up.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Lead 7439-92-1	TWA: 0.05 mg/m <sup>3</sup>	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> Pb Action Level: 30 µg/m <sup>3</sup> Poison; See 29 CFR 1910.1025 Action Level: 30 µg/m <sup>3</sup> Pb Poison; See 29 CFR 1910.1025	IDLH: 100 mg/m <sup>3</sup> IDLH: 100 mg/m <sup>3</sup> Pb TWA: 0.050 mg/m <sup>3</sup> TWA: 0.050 mg/m <sup>3</sup> Pb	
Sulfuric acid 7664-93-9	TWA: 0.2 mg/m <sup>3</sup> thoracic particulate matter	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 15 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	
Antimony 7440-36-0	TWA: 0.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> Sb	TWA: 0.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> Sb (vacated) TWA: 0.5 mg/m <sup>3</sup> (vacated) TWA: 0.5 mg/m <sup>3</sup> Sb	IDLH: 50 mg/m <sup>3</sup> IDLH: 50 mg/m <sup>3</sup> Sb TWA: 0.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> Sb	
Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Lead 7439-92-1	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>
Sulfuric acid 7664-93-9	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>
Antimony 7440-36-0	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>



**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

#### Appropriate engineering controls

**Engineering controls** Showers  
Eyewash stations  
Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Face protection shield.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Do not breathe dust. Take off contaminated clothing and wash before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

**Physical state** Solid  
**Appearance** Varies  
**Odor** Odorless  
**Color** No information available  
**Odor Threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	2	
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.27	
Water Solubility	Reacts with water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	NA	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known

Dynamic viscosity	No data available	None known
-------------------	-------------------	------------

**Other Information**

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Liquid Density</b>	No information available
<b>Bulk Density</b>	No information available
<b>Particle Size</b>	No information available
<b>Particle Size Distribution</b>	No information available

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Exposure to air or moisture over prolonged periods. Excessive heat.
<b>Incompatible materials</b>	Oxidizing agent. Acids. Bases.
<b>Hazardous Decomposition Products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture:
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. Toxic by inhalation.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Information on toxicological effects

**Symptoms** Redness. Burning. May cause blindness. Coughing and/ or wheezing. Difficulty in breathing.

Numerical measures of toxicity**Acute Toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	624.00 mg/kg
<b>ATEmix (inhalation-gas)</b>	4,500.00 mg/L
<b>ATEmix (inhalation-dust/mist)</b>	0.66 mg/L
<b>ATEmix (inhalation-vapor)</b>	11.00 mg/L

**Unknown acute toxicity** 100 % of the mixture consists of ingredient(s) of unknown toxicity  
 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 26 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 26 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Sulfuric acid	= 2140 mg/kg ( Rat )	-	= 510 mg/m <sup>3</sup> ( Rat ) 2 h
Antimony	= 7 g/kg ( Rat )	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes burns.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lead 7439-92-1	A3	Group 2A	Reasonably Anticipated	X
Sulfuric acid 7664-93-9	A2	Group 1	Known	X

**Legend****ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**



X - Present

**Reproductive toxicity** Classification based on data available for ingredients. Contains a known or suspected reproductive toxin. May cause harm to breastfed babies.

**STOT - single exposure** No information available.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead	-	96h LC50: = 0.44 mg/L (Cyprinus carpio) 96h LC50: = 1.17 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.32 mg/L (Oncorhynchus mykiss)	-	48h EC50: = 600 µg/L
Sulfuric acid	-	96h LC50: > 500 mg/L (Brachydanio rerio)	-	24h EC50: = 29 mg/L

**Persistence and Degradability** No information available.

**Bioaccumulation** There is no data for this product.

**Mobility** No information available.

**Other adverse effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**US EPA Waste Number** D008 D002

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Antimony 7440-36-0				Toxic waste waste number K021 Waste description: Aqueous spent antimony catalyst waste from fluoromethanes production.



**California Hazardous Waste Codes 792**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lead 7439-92-1	Toxic
Sulfuric acid 7664-93-9	Toxic Corrosive
Antimony 7440-36-0	Toxic

**14. TRANSPORT INFORMATION**

**DOT**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8  
**Emergency Response Guide Number** 154

**TDG**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to TDG.  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8

**MEX**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8

**ICAO**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8

**IATA**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**ERG Code** 8L  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8

**IMDG/IMO**

**UN-No.** UN2794  
**Proper Shipping Name** BATTERIES, WET, FILLED WITH ACID  
**Hazard Class** 8  
**EmS-No.** F-A, S-B  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO  
**Description** UN2794, BATTERIES, WET, FILLED WITH ACID, 8



**RID**

<b>UN-No.</b>	UN2794
<b>Proper Shipping Name</b>	BATTERIES, WET, FILLED WITH ACID
<b>Hazard Class</b>	8
<b>Classification code</b>	C11
<b>Description</b>	UN2794, BATTERIES, WET, FILLED WITH ACID, 8
<b>ADR/RID-Labels</b>	8

**ADR**

<b>UN-No.</b>	UN2794
<b>Proper Shipping Name</b>	BATTERIES, WET, FILLED WITH ACID
<b>Hazard Class</b>	8
<b>Classification code</b>	C11
<b>Tunnel restriction code</b>	(E)
<b>Description</b>	UN2794, BATTERIES, WET, FILLED WITH ACID, 8, (E)

**ADN**

<b>UN-No.</b>	UN2794
<b>Proper Shipping Name</b>	BATTERIES, WET, FILLED WITH ACID
<b>Hazard Class</b>	8
<b>Classification code</b>	C11
<b>Special Provisions</b>	295, 598
<b>Description</b>	UN2794, BATTERIES, WET, FILLED WITH ACID, 8
<b>Hazard Labels</b>	8
<b>Limited Quantity</b>	1 L

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

**International Inventories**

<b>TSCA</b>	Contact supplier for inventory compliance status.
<b>DSL/NDL</b>	Contact supplier for inventory compliance status.
<b>EINECS/ELINCS</b>	Contact supplier for inventory compliance status.
<b>ENCS</b>	Contact supplier for inventory compliance status.
<b>KECL</b>	Contact supplier for inventory compliance status.
<b>PICCS</b>	Contact supplier for inventory compliance status.
<b>AICS</b>	Contact supplier for inventory compliance status.

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Percent	SARA 313 - Threshold Values %
Lead - 7439-92-1	7439-92-1	70	0.1
Sulfuric acid - 7664-93-9	7664-93-9	26	1.0
Antimony - 7440-36-0	7440-36-0	4	1.0

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Lead 7439-92-1		X	X	
Sulfuric acid 7664-93-9	1000 lb			X
Antimony 7440-36-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Lead 7439-92-1	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Sulfuric acid 7664-93-9	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ
Antimony 7440-36-0	5000 lb 10 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ RQ 10 lb final RQ RQ 4.54 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Sulfuric acid - 7664-93-9	Carcinogen

**U.S. State Right-to-Know Regulations**



Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lead 7439-92-1	X	X	X	X	X
Sulfuric acid 7664-93-9	X	X	X	X	X
Antimony 7440-36-0	X	X	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health hazards 1 Flammability 0 Instability 0 Physical and Chemical Properties -  
**HMIS** Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

**Prepared By** Product Stewardship  
 23 British American Blvd.  
 Latham, NY 12110  
 1-800-572-6501

**Issuing Date** 20-Jul-2017

**Revision Date** 20-Jul-2017

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

