



Marvel Air Tool Oil

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
US GHS SDS
Revision Date: 03/15/2022 Date of Issue: 03/23/2021

Version: 2.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Marvel Air Tool Oil

Product Code: MM85R1 (50100), MM080R (50093), 50099

1.2. Intended Use of the Product

Use of the Substance/Mixture: Lubricant for Air Driven Motors and Tools

1.3. Name, Address, and Telephone of the Responsible Party

Manufacturer

Marvel Oil Company, Inc.

2250 W. Pinehurst Blvd., Suite 150

Addison, IL 60101-6103

Phone Number: 1(630)455-3700

Toll-Free Number: 1(800)232-9596

1.4. Emergency Telephone Number

Emergency Number

: ChemTel LLC

1-800-255-3924 (US and Canada)

1-813-248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Flam. Liq. 3 H226

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Repr. 2 H361

STOT SE 3 H336

Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS02



GHS07



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H361 - Suspected of damaging fertility or the unborn child.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, or spray.

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see section 4 on this SDS).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Petroleum distillates, hydrotreated light	Hydrotreated Light Alkanes / Distillates (petroleum), hydrotreated light / Distillates, petroleum, hydrotreated light / Hydrotreated light distillate / Kerosene, hydrotreated	(CAS-No.) 64742-47-8	<25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Phosphoric acid, tris(methylphenyl) esters	Tricresyl Phosphate / Phosphoric acid, tris(methylphenyl) ester / Phosphoric acid, tritolyl ester / Tricresyl phosphate	(CAS-No.) 1330-78-5	<1	Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
o-Dichlorobenzene	Ortho Dichlorobenzene / Benzene, 1,2-dichloro- / o-DCB / Dichlorobenzene, o- / Dichlorobenzene, 1,2- / 1,2-Dichlorobenzene	(CAS-No.) 95-50-1	<1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Benzene, 1,4-dichloro-	p-Dichlorobenzene / Benzene, p-dichloro- / para-Dichlorobenzene / 1,4-Dichlorobenzene	(CAS-No.) 106-46-7	<0.001	Skin Irrit. 2, H315 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
------------------------	---	--------------------	--------	--

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. If exposed or concerned: Get medical advice/attention. Immediately drench affected area with water for at least 15 minutes.

First-aid Measures After Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Causes skin irritation. Causes serious eye irritation. May cause drowsiness and dizziness. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: Suspected of damaging fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Acrid smoke and irritating fumes. Phosphorus oxides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Eliminate ignition sources first, then ventilate the area.

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Do not get in eyes, on skin, or on clothing. Do NOT breathe (vapors, mist, or spray). Obtain special instructions before use. Take precautionary measures against static discharge. Do not handle until all safety precautions have been read and understood. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Lubricant for Air Driven Motors and Tools

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Benzene, 1,4-dichloro- (106-46-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	10 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA IDLH	IDLH [ppm]	150 ppm
USA OSHA	OSHA PEL (TWA) [1]	450 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	75 ppm
o-Dichlorobenzene (95-50-1)		
USA ACGIH	ACGIH OEL TWA [ppm]	25 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	50 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (Ceiling)	300 mg/m ³
USA NIOSH	NIOSH REL C [ppm]	50 ppm
USA IDLH	IDLH [ppm]	200 ppm
USA OSHA	OSHA PEL (Ceiling)	300 mg/m ³
USA OSHA	OSHA PEL C [ppm]	50 ppm

8.2. Exposure Controls


Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Personal Protective Equipment	: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.
	
Materials for Protective Clothing	: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.
Hand Protection	: Wear protective gloves.
Eye and Face Protection	: Chemical safety goggles.
Skin and Body Protection	: Wear suitable protective clothing.
Respiratory Protection	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear red liquid
Odor	: Typical oily
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: 53 °C (Closed Cup) (127.4 °F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.876
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Viscosity, Kinematic	: 2 – 3 cSt (@100°C (212°F))

9.2. Other Information

VOC content (California)	: 24.92 %
% NVM by Weight	: 75 %

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability:** Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition may produce: Carbon oxides (CO, CO₂). Oxides of phosphorus. Acrid smoke and irritating fumes.

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Benzene, 1,4-dichloro- (106-46-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 6000 mg/kg
LC50 Inhalation Rat	> 5070 mg/m ³ (Exposure time: 4 h)
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
o-Dichlorobenzene (95-50-1)	
LD50 Oral Rat	1516 mg/kg
LD50 Dermal Rabbit	> 10 g/kg
LC50 Inhalation Rat	9.2 mg/l (Exposure time: 6 h)
ATE (Dust/Mist)	1.50 mg/l/4h
Phosphoric acid, tris(methylphenyl) esters (1330-78-5)	
LD50 Oral Rat	> 20000 mg/kg
LD50 Dermal Rabbit	> 10000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified (The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.)

Benzene, 1,4-dichloro- (106-46-7)	
IARC group	2B
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen, Evidence of Carcinogenicity.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
o-Dichlorobenzene (95-50-1)	
IARC group	3

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: Suspected of damaging fertility or the unborn child.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Benzene, 1,4-dichloro- (106-46-7)	
LC50 Fish 1	18 – 50 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	0.7 mg/l
LC50 Fish 2	4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
NOEC Chronic Crustacea	0.1 mg/l

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
o-Dichlorobenzene (95-50-1)	
LC50 Fish 1	8.23 – 10.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	0.74 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	5.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC Chronic Crustacea	0.1 mg/l
Phosphoric acid, tris(methylphenyl) esters (1330-78-5)	
LC50 Fish 1	0.1 – 0.22 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 Fish 2	0.21 – 0.32 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

12.2. Persistence and Degradability

Marvel Air Tool Oil	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Marvel Air Tool Oil	
Bioaccumulative Potential	Not established.

Benzene, 1,4-dichloro- (106-46-7)	
Partition coefficient n-octanol/water (Log Pow)	3.4

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF Fish 1	61 – 159
o-Dichlorobenzene (95-50-1)	
BCF Fish 1	90 – 260
Partition coefficient n-octanol/water (Log Pow)	3.43

12.4. **Mobility in Soil** No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

This product meets the limited quantity exceptions as specified in the 49 CFR as Not Regulated as dangerous goods when shipped in accordance with any applicable subparts that may apply.

Proper Shipping Name : FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates, hydrotreated light ; o-Dichlorobenzene)
Hazard Class : 3
Identification Number : UN1993
Label Codes : 3
Packing Group : III
Marine Pollutant : Marine pollutant
ERG Number : 128



14.2. In Accordance with IMDG

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S. (Contains Petroleum distillates, hydrotreated light ; o-Dichlorobenzene)

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Hazard Class : 3
Identification Number : UN1993
Packing Group : III
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Marine Pollutant : Marine pollutant



14.3. In Accordance with IATA

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S. (Contains Petroleum distillates, hydrotreated light ; o-Dichlorobenzene)
Packing Group : III
Identification Number : UN1993
Hazard Class : 3
Label Codes : 3
ERG Code (IATA) : 3L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

Marvel Air Tool Oil	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Reproductive toxicity Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Aspiration hazard
Benzene, 1,4-dichloro- (106-46-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	0.1 %
o-Dichlorobenzene (95-50-1)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %
Phosphoric acid, tris(methylphenyl) esters (1330-78-5)	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed Section 4 test rule under TSCA.

15.2. US State Regulations

Benzene, 1,4-dichloro- (106-46-7)	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
o-Dichlorobenzene (95-50-1)	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Phosphoric acid, tris(methylphenyl) esters (1330-78-5)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

California Proposition 65



WARNING: This product can expose you to Benzene, 1,4-dichloro-, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Benzene, 1,4-dichloro- (106-46-7)	X			

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 03/15/2022
Formula Identification Number	: 40740
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:


Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Marvel Air Tool Oil

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

NFPA Health Hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA Fire Hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
NFPA Reactivity Hazard	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS III Rating	
Health	: 2 Moderate Hazard
Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard



Legal disclaimer: ©Marvel Oil Company, Inc. All rights reserved.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date issued. No warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the responsibility of the user or processor to satisfy themselves as to the suitability of such information for their own particular circumstances, conditions or use, including transportation, storage and disposal which are outside of our control.

SDS US (GHS HazCom)