



# SAFETY DATA SHEET

## 1. Identification

|  |   |
|--|---|
| Product identifier                                     | SP-350™ Corrosion Inhibitor                       |
| Other means of identification                          |   |
| Product code   | 03262   |
| Recommended use  | Lubricant and corrosion Inhibitor                 |
| Recommended restrictions                               | None known.                                       |
| Manufacturer/Importer/Supplier/Distributor information |   |
| Manufactured or sold by:                               |   |
| Company name   | CRC Industries, Inc.                              |
| Address  | 885 Louis Dr.<br>Warminster, PA 18974 US          |
| Telephone  |   |
| General Information                                    | 215-674-4300                                      |
| Technical Assistance                                   | 800-521-3168                                      |
| Customer Service                                       | 800-272-4620                                      |
| 24-Hour Emergency (CHEMTREC)                           | 800-424-9300 (US)<br>703-527-3887 (International) |
| Website  | www.crcindustries.com                             |

## 2. Hazard(s) identification

|                       |  |  |
|-----------------------|--|--|
| Physical hazards      | Flammable aerosols<br>Gases under pressure   | Category 1<br>Compressed gas   |
| Health hazards        | Skin corrosion/irritation<br>Serious eye damage/eye irritation<br>Specific target organ toxicity, single exposure<br>Aspiration hazard | Category 2<br>Category 2A<br>Category 3 narcotic effects<br>Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard   | Category 2   |
| OSHA defined hazards  | Not classified.  |  |
| Label elements        |  |  |



Signal word                    Danger

Hazard statement            Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life.

### Precautionary statement

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Avoid breathing gas, mist or vapor. Wash hands thoroughly after handling. Wear protective gloves and eye/face protection. Avoid release to the environment.

#### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

|  |  |
|--|--|
| <b>Storage</b>                                   | Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. |
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national regulations.  |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | None known.  |
| <b>Supplemental information</b>                  | 52.84% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.  |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name   | Common name and synonyms | CAS number | %       |
|---|--------------------------|------------|---------|
| Distillates (petroleum), Hydrotreated Light               |                          | 64742-47-8 | 30 - 40 |
| Distillates (petroleum), Solvent-refined Heavy Paraffinic |                          | 64741-88-4 | 20 - 30 |
| Stoddard Solvent  |                          | 8052-41-3  | 10 - 20 |
| n-Butyl stearate  |                          | 123-95-5   | 3 - 5   |
| Carbon dioxide  |                          | 124-38-9   | 1 - 3   |
| Fatty Acids, C18-unsatd., Dimers                          |                          | 61788-89-4 | 1 - 3   |
| Petrolatum  |                          | 8009-03-8  | 1 - 3   |
| Sodium petroleum sulfonate                                |                          | 68608-26-4 | 1 - 3   |
| n-Octane  |                          | 111-65-9   | < 0.2   |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.   |
| <b>Skin contact</b>   | Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.   |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.             |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness. May cause redness and pain. |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.  |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.  |

### 5. Fire-fighting measures

|  |   |
|--|---|
| <b>Suitable extinguishing media</b>                                  | Alcohol resistant foam. Water. Water spray. Dry powder. Dry chemicals. Carbon dioxide (CO2).  |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame.   |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.  |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>General fire hazards</b>  | Extremely flammable aerosol.  |

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage**

**Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**U.S. - OSHA**

**Components**

**Type**

**Value**

**Form**

Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)

TWA

5 mg/m3

Respirable

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

**Components**

**Type**

**Value**

**Form**

Carbon dioxide (CAS 124-38-9)

PEL

9000 mg/m3

Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)

PEL

5000 ppm

5 mg/m3

Mist.

n-Octane (CAS 111-65-9)

PEL

2000 mg/m3

500 ppm

2350 mg/m3

500 ppm

Petrolatum (CAS 8009-03-8)

PEL

5 mg/m3

Mist.

Stoddard Solvent (CAS 8052-41-3)

PEL

2900 mg/m3

500 ppm

| ACGIH Components                                  | Type | Value    | Form       |
|---|------|----------|------------|
| Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4) | STEL | 10 mg/m3 | Respirable |
|   | TWA  | 5 mg/m3  | Respirable |

| US. ACGIH Threshold Limit Values Components                                | Type | Value     | Form                |
|--|------|-----------|---------------------|
| Carbon dioxide (CAS 124-38-9)  | STEL | 30000 ppm |                     |
|  | TWA  | 5000 ppm  |                     |
| Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4) | TWA  | 5 mg/m3   | Inhalable fraction. |
| n-Butyl stearate (CAS 123-95-5)  | TWA  | 10 mg/m3  |                     |
| n-Octane (CAS 111-65-9)  | TWA  | 300 ppm   |                     |
| Petrolatum (CAS 8009-03-8)   | TWA  | 5 mg/m3   | Inhalable fraction. |
| Stoddard Solvent (CAS 8052-41-3)   | TWA  | 100 ppm   |                     |

| US. NIOSH: Pocket Guide to Chemical Hazards Components                     | Type    | Value                               | Form  |
|--|---------|-------------------------------------|-------|
| Carbon dioxide (CAS 124-38-9)  | STEL    | 54000 mg/m3                         |       |
|  | TWA     | 30000 ppm<br>9000 mg/m3<br>5000 ppm |       |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)               | TWA     | 100 mg/m3                           |       |
| Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4) | STEL    | 10 mg/m3                            | Mist. |
|  | TWA     | 5 mg/m3                             | Mist. |
| n-Octane (CAS 111-65-9)  | Ceiling | 1800 mg/m3<br>385 ppm               |       |
|  | TWA     | 350 mg/m3<br>75 ppm                 |       |
| Petrolatum (CAS 8009-03-8)   | STEL    | 10 mg/m3                            | Mist. |
|  | TWA     | 5 mg/m3                             | Mist. |
| Stoddard Solvent (CAS 8052-41-3)   | Ceiling | 1800 mg/m3                          |       |
|  | TWA     | 350 mg/m3                           |       |

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear protective gloves such as neoprene or nitrile.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

---

|   |                                 |
|---|---------------------------------|
| <b>Appearance</b>                                   |                                 |
| Physical state                                      | Liquid.                         |
| Form  | Aerosol.                        |
| Color   | Tan. Cream.                     |
| <b>Odor</b>   | Petroleum.                      |
| <b>Odor threshold</b>                               | Not available.                  |
| <b>pH</b>   | Not available.                  |
| <b>Melting point/freezing point</b>                 | -94 °F (-70 °C) estimated       |
| <b>Initial boiling point and boiling range</b>      | 315 °F (157.2 °C) estimated     |
| <b>Flash point</b>                                  | 144 °F (62.2 °C) Tag Closed Cup |
| <b>Evaporation rate</b>                             | Slow                            |
| <b>Flammability (solid, gas)</b>                    | Not available.                  |
| <b>Upper/lower flammability or explosive limits</b> |                                 |
| Flammability limit - lower (%)                      | 0.6 % estimated                 |
| Flammability limit - upper (%)                      | 6 % estimated                   |
| <b>Vapor pressure</b>                               | 1625.3 hPa estimated            |
| <b>Vapor density</b>                                | > 1 (air = 1)                   |
| <b>Relative density</b>                             | 0.87 estimated                  |
| <b>Solubility (water)</b>                           | Not available.                  |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                  |
| <b>Auto-ignition temperature</b>                    | 410 °F (210 °C) estimated       |
| <b>Decomposition temperature</b>                    | Not available.                  |
| <b>Viscosity (kinematic)</b>                        | Not available.                  |
| <b>Percent volatile</b>                             | 78 % estimated                  |

## 10. Stability and reactivity

---

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.  |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong oxidizing agents.   |
| <b>Hazardous decomposition products</b>   | Carbon oxides. Sulfur compounds.   |

## 11. Toxicological information

---

### Information on likely routes of exposure

|   |  |
|---|--|
| <b>Ingestion</b>  | May be fatal if swallowed and enters airways.  |
| <b>Inhalation</b>   | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.  |
| <b>Skin contact</b>   | Causes skin irritation.  |
| <b>Eye contact</b>  | Causes serious eye irritation.   |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. |

### Information on toxicological effects

|                       |   |
|-----------------------|---|
| <b>Acute toxicity</b> | May be fatal if swallowed and enters airways. Narcotic effects. |
|-----------------------|---|

| Product                     | Species | Test Results   |
|-----------------------------|---------|--|
| SP-350™ Corrosion Inhibitor |         |  |
| <b>Acute</b>                |         |  |
| <i>Dermal</i>               |         |  |
| LD50                        | Rabbit  | 4824.8989 mg/kg estimated                                    |
|                             | Rat     | 70373.9844 mg/kg estimated                                   |
| <i>Inhalation</i>           |         |  |
| LC50                        | Rat     | 49261.7891 ppm, 4 hours estimated<br>182.8879 mg/l estimated |
| <i>Oral</i>                 |         |  |
| LD50                        | Rat     | 8587.7617 mg/kg estimated                                    |
| <b>Subchronic</b>           |         |  |
| <i>Oral</i>                 |         |  |
| LD50                        | Rat     | 670.8857 g/kg, 14 days estimated                             |

\* Estimates for product may be based on additional component data not shown.

|   |  |
|---|--|
| <b>Skin corrosion/irritation</b>                          | Causes skin irritation.  |
| <b>Serious eye damage/eye irritation</b>                  | Causes serious eye irritation.   |
| <b>Respiratory sensitization</b>                          | Not available.   |
| <b>Skin sensitization</b>                                 | This product is not expected to cause skin sensitization.  |
| <b>Germ cell mutagenicity</b>                             | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>                                    | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.                                  |
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects.                                     |
| <b>Specific target organ toxicity - single exposure</b>   | Narcotic effects.  |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.  |
| <b>Aspiration hazard</b>                                  | May be fatal if swallowed and enters airways.  |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful.   |

## 12. Ecological information

| Product  | Species                             | Test Results                         |
|--|-------------------------------------|--------------------------------------|
| Ecotoxicity Toxic to aquatic life.                           |                                     |                                      |
| SP-350™ Corrosion Inhibitor                                  |                                     |                                      |
| <i>Acute</i>   |                                     |                                      |
| Fish   | LC50 Fish                           | 4247.5723 ppm, 96 hours estimated    |
| <b>Components</b>  |                                     |                                      |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) |                                     |                                      |
| <b>Aquatic</b>   |                                     |                                      |
| <i>Acute</i>   |                                     |                                      |
| Fish   | LC50 Bluegill (Lepomis macrochirus) | 2.2 mg/l, 96 hours                   |
| Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)            |                                     |                                      |
| <i>Acute</i>   |                                     |                                      |
| Crustacea  | NOEL Daphnia                        | 1000 mg/l, 48 hours loading rate WAF |
| Fish   | NOEL Fish                           | 1000 mg/l, 96 hours loading rate WAF |

\* Estimates for product may be based on additional component data not shown.

|  |  |
|--|--|
| <b>Persistence and degradability</b>                     | No data is available on the degradability of this product. |
| <b>Bioaccumulative potential</b>                         | No data available.   |
| <b>Partition coefficient n-octanol / water (log Kow)</b> |  |
| Fatty Acids, C18-unsatd., Dimers                         | 1 - 2.5, logKow  |
| n-Octane   | 5.18   |
| Stoddard Solvent   | 3.16 - 7.15  |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

---

**Disposal of waste from residues / unused products** The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** Not regulated.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

---

#### DOT

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, limited quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** N82  
**Packaging exceptions** 306  
**Packaging non bulk** None  
**Packaging bulk** None

#### IATA

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, limited quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**ERG Code** 10L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.

#### IMDG

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, LIMITED QUANTITY  
**Transport hazard class(es)**  
**Class** 2  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

### 15. Regulatory information

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
Not regulated.

**SARA 304 Emergency release notification**  
Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**  
Not listed.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**  
Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

|                          |                        |
|--------------------------|------------------------|
| <b>Section 311/312</b>   | Immediate Hazard - Yes |
| <b>Hazard categories</b> | Delayed Hazard - No    |
|                          | Fire Hazard - Yes      |
|                          | Pressure Hazard - Yes  |
|                          | Reactivity Hazard - No |

|   |    |
|---|----|
| <b>SARA 302 Extremely hazardous substance</b> | No |
|---|----|

**US state regulations****US. New Jersey RTK - Substances: Listed substance**

Carbon dioxide (CAS 124-38-9)  
 n-Octane (CAS 111-65-9)  
 Stoddard Solvent (CAS 8052-41-3)

**US. Massachusetts RTK - Substance List**

Carbon dioxide (CAS 124-38-9)  
 Stoddard Solvent (CAS 8052-41-3)

**US. Pennsylvania RTK - Hazardous Substances**

Carbon dioxide (CAS 124-38-9)  
 Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)  
 n-Octane (CAS 111-65-9)  
 Stoddard Solvent (CAS 8052-41-3)

**US. Rhode Island RTK**

None.

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**Volatile organic compounds (VOC) regulations****EPA**

|                                       |        |
|---------------------------------------|--------|
| <b>VOC content (40 CFR 51.100(s))</b> | 88.3 % |
|---------------------------------------|--------|

|  |               |
|--|---------------|
| <b>Consumer products (40 CFR 59, Subpt. C)</b> | Not regulated |
|--|---------------|

**State**

|                          |   |
|--------------------------|---|
| <b>Consumer products</b> | This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states. |
|--------------------------|---|

|                         |        |
|-------------------------|--------|
| <b>VOC content (CA)</b> | 24.1 % |
|-------------------------|--------|

|                          |        |
|--------------------------|--------|
| <b>VOC content (OTC)</b> | 24.1 % |
|--------------------------|--------|

**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada               | Domestic Substances List (DSL)   | No                     |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |



| Country(s) or region        | Inventory name  | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Korea                       | Existing Chemicals List (ECL)                                     | No                     |
| New Zealand                 | New Zealand Inventory   | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                     | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

|                            |  |
|----------------------------|--|
| <b>Issue date</b>          | 11-11-2013   |
| <b>Prepared by</b>         | Allison Cho  |
| <b>Version #</b>           | 01   |
| <b>Further information</b> | CRC # 527J-K   |
| <b>HMIS® ratings</b>       | Health: 2<br>Flammability: 3<br>Physical hazard: 0<br>Personal protection: B   |
| <b>NFPA ratings</b>        | Health: 2<br>Flammability: 3<br>Instability: 0   |
| <b>Disclaimer</b>          | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries. |