



# XIAMETER(TM) Material Safety Data Sheet

Page: 1 of 7  
Version: 1.1

Revision Date: 2003/07/18

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

### 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

XIAMETER(TM). The measure of value.  
Dow Corning Corporation  
South Saginaw Road  
Midland, Michigan 48686

**24 Hour Emergency Telephone: (989) 496-5900**  
Customer Service: (989) 496-6000  
Product Disposal Information: (989) 496-6315  
CHEMTREC: (800) 424-9300

MSDS No.: 04000237

Revision Date: 2003/07/18

Generic Description: Silicone Sealant  
Physical Form: Paste  
Color: White  
Odor: Not available

NFPA Profile: Health 2 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

### 2. OSHA HAZARDOUS COMPONENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
9016-45-9	1.0 - 5.0	Polyethylene glycol nonylphenol

The above components are hazardous as defined in 29 CFR 1910.1200.

### 3. EFFECTS OF OVEREXPOSURE

#### Acute Effects


Eye: Direct contact may cause moderate irritation.  
Skin: May cause moderate irritation.  
Inhalation: Irritates respiratory passages very slightly.  
Oral: Low ingestion hazard in normal use.

#### Prolonged/Repeated Exposure Effects

Skin: No known applicable information.  
Inhalation: No known applicable information.  
Oral: No known applicable information.

#### Signs and Symptoms of Overexposure

No known applicable information.



# XIAMETER(TM) Material Safety Data Sheet

Page: 2 of 7

Version: 1.1

Revision Date: 2003/07/18

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

### Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

### 4. FIRST AID MEASURES

Eye:	Immediately flush with water for 15 minutes. Get medical attention.
Skin:	Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.
Inhalation:	No first aid should be needed.
Oral:	No first aid should be needed.
Comments:	Treat according to person's condition and specifics of exposure.

### 5. FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

### Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen oxides. Sulfur oxides. Metal oxides. Quartz. Formaldehyde.

### 6. ACCIDENTAL RELEASE MEASURES

# XIAMETER(TM) Material Safety Data Sheet

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

**Containment/Clean up:** Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note:** See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

### 7. HANDLING AND STORAGE

Use with adequate ventilation. Avoid eye contact. Avoid skin contact.

Use reasonable care and store away from oxidizing materials.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Component Exposure Limits

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
9016-45-9	Polyethylene glycol nonylphenol	AIHA WEEL: TWA 10 mg/m <sup>3</sup> , aerosol.

#### Engineering Controls

Local Ventilation: None should be needed.  
General Ventilation: Recommended.

#### Personal Protective Equipment for Routine Handling

**Eyes:** Use proper protection - safety glasses as a minimum.

**Skin:** Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.


**Suitable Gloves:** Silver Shield(R). 4H(R).

**Inhalation:** No respiratory protection should be needed.

**Suitable Respirator:** None should be needed.

#### Personal Protective Equipment for Spills

# XIAMETER(TM) Material Safety Data Sheet



Page: 4 of 7

Version: 1.1

Revision Date: 2003/07/18

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

Eyes:	Use proper protection - safety glasses as a minimum.
Skin:	Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.
Inhalation/Suitable Respirator:	No respiratory protection should be needed.
Precautionary Measures:	Avoid eye contact. Avoid skin contact. Use reasonable care.
Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.	

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Paste
Color:	White
Odor:	Not available
Specific Gravity @ 25°C:	1.35
Viscosity:	Not determined.
Freezing/Melting Point:	Not determined.
Boiling Point:	Not determined.
Vapor Pressure @ 25°C:	Not determined.
Vapor Density:	Not determined.
Solubility in Water:	Not determined.
pH:	Not determined.
Volatile Content:	Not determined.

Note: The above information is not intended for use in preparing product specifications.

### 10. STABILITY AND REACTIVITY


Chemical Stability:	Stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to Avoid:	None.
Materials to Avoid:	Oxidizing material can cause a reaction.

### 11. TOXICOLOGICAL INFORMATION

#### Special Hazard Information on Components

No known applicable information.

### 12. ECOLOGICAL INFORMATION



# XIAMETER(TM) Material Safety Data Sheet

Page: 5 of 7

Version: 1.1

Revision Date: 2003/07/18

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

### Environmental Fate and Distribution

Complete information is not yet available.

### Environmental Effects

Complete information is not yet available.

### Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

#### Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

## 13. DISPOSAL CONSIDERATIONS

### RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

Call (989) 496-6315, if additional information is required.

## 14. TRANSPORT INFORMATION

### DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

### Ocean Shipment (IMDG)

Not subject to IMDG code.

### Air Shipment (IATA)

Not subject to IATA regulations.

## 15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA

# XIAMETER(TM) Material Safety Data Sheet



## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

Inventory of Chemical Substances.

### EPA SARA Title III Chemical Listings

#### Section 302 Extremely Hazardous Substances:

None.

#### Section 304 CERCLA Hazardous Substances:

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
27176-87-0	0.4	Dodecylbenzene sulfonic acid
109-89-7	0.2	Diethylamine
58-36-6	0.01	10,10-Oxydiphenoxarsine

#### Section 312 Hazard Class:

Acute: Yes  
Chronic: No  
Fire: No  
Pressure: No  
Reactive: No

#### Section 313 Toxic Chemicals:

None present or none present in regulated quantities.

### Supplemental State Compliance Information

#### California

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.


None known.

#### Massachusetts

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1317-65-3	40.0 - 70.0	Limestone
58-36-6	<0.1	10,10-Oxydiphenoxarsine
7664-93-9	<0.1	Sulfuric acid

#### New Jersey

# XIAMETER(TM) Material Safety Data Sheet



Page: 7 of 7

Version: 1.1

Revision Date: 2003/07/18

## DAP(R) PAINTABLE SILICONE RUBBER SEALANT WHITE, 8654

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1317-65-3	40.0 - 70.0	Limestone
70131-67-8	30.0 - 60.0	Dimethyl siloxane, hydroxy-terminated
7732-18-5	15.0 - 40.0	Water
9016-45-9	1.0 - 5.0	Polyethylene glycol nonylphenol
14808-60-7	<=0.6	Quartz

### Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1317-65-3	40.0 - 70.0	Limestone
70131-67-8	30.0 - 60.0	Dimethyl siloxane, hydroxy-terminated
7732-18-5	15.0 - 40.0	Water

### 16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

XIAMETER(TM) is a trademark of Dow Corning Corporation

Get access to the new measure of value at: <http://www.xiameter.com>