

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 1/10
(30356025/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Elastocast AD52

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component

Suitable for use in industrial sector: Polymers industry; chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: plasticizers

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Hazard Statement:

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 2/10
(30356025/SDS_GEN_US/EN)

H412 Harmful to aquatic life with long lasting effects.
H401 Toxic to aquatic life.

Precautionary Statements (Prevention):
P273 Avoid release to the environment.

Precautionary Statements (Disposal):
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
27138-31-4	>= 50.0 - <= 100.0%	Propanol, oxybis-, dibenzoate

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention. Assist breathing with a ventilator bag or ventilator.

If on skin:

After contact with skin, wash immediately with plenty of water.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 3/10
(30356025/SDS_GEN_US/EN)

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, carbon dioxide,
The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Use personal protective clothing. Sources of ignition should be kept well clear.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Handle and open container with care.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame.

Conditions for safe storage, including any incompatibilities

Segregate from oxidants. Segregate from acids and bases. Segregate from foods and animal feeds.

Suitable materials for containers: Stainless steel 1.4401, Stainless steel 1.4301 (V2), High density polyethylene (HDPE), Low density polyethylene (LDPE), glass, Stove-lacquer RDL 50, Stove-lacquer KNS L-15, Carbon steel (Iron)

Unsuitable materials for containers: Paper/Fibreboard

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 4/10
(30356025/SDS_GEN_US/EN)

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep only in the original container.

8. Exposure Controls/Personal Protection

Does not contain components with substance specific occupational exposure limits.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	ester-like	
Odour threshold:	not applicable	
Colour:	off-white	
pH value:	approx. 6 - 8 (20 °C)	
Freezing point:	-20 °C	
boiling temperature:	> 300 °C	
Sublimation point:	No applicable information available.	
Flash point:	192 °C	(ASTM D56)
Flammability:	not readily ignited	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 400 °C	
Vapour pressure:	< 0.1 hPa (25 °C)	

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 5/10
(30356025/SDS_GEN_US/EN)

Density:	1.12 g/cm ³ (20 °C)
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	3.9
Self-ignition temperature:	not self-igniting
Thermal decomposition:	> 230 °C No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	approx. 110 mPa.s (25 °C)
Viscosity, kinematic:	No applicable information available.
Solubility in water:	0.00869 g/l (20 °C) insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	342.39 g/mol
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Avoid extreme heat.

Incompatible materials

acids, bases, oxidizing agents

Hazardous decomposition products

Decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
> 230 °C
No decomposition if stored and handled as prescribed/indicated.

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 6/10
(30356025/SDS_GEN_US/EN)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Virtually nontoxic after a single ingestion.

Oral

Type of value: LD50

Species: rat

Value: 3,914 mg/kg

Inhalation

Type of value: LC50

Species: rat

Value: > 200 mg/l

Exposure time: 4 h

Dermal

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion

Assessment of irritating effects: Not irritating to the eyes. Not irritating to the skin.

Skin

Species: rabbit

Result: non-irritant

Eye

Species: rabbit

Result: Slightly irritating.

Sensitization

Assessment of sensitization: The chemical structure does not suggest a sensitizing effect.

Species: guinea pig

Result: Non-sensitizing.

Aspiration Hazard

No aspiration hazard expected.

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 7/10
(30356025/SDS_GEN_US/EN)

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. Repeated inhalative uptake of the substance did not cause substance-related effects. Repeated oral uptake of the substance did not cause substance-related effects.
Experimental/calculated data: rat oral feed 90 d
NOAEL: 1,000 mg/kg

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect.

Other Information

No experimental evidence available for genotoxicity in vivo (micro-nucleus test negativ). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Toxicity to fish

LC50 (96 h) 3.7 mg/l

Aquatic invertebrates

(48 h) 19.3 mg/l, Daphnia magna

Aquatic plants

EL50 (72 h) 4.9 mg/l (growth rate), Desmodemus subspicatus

No observed effect concentration (72 h) 1.0 mg/l (growth rate), Desmodemus subspicatus

Microorganisms/Effect on activated sludge

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 8/10
(30356025/SDS_GEN_US/EN)

Toxicity to microorganisms

bacterium/EC50: > 10 mg/l

activated sludge/EC0: 100 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Readily biodegradable (according to OECD criteria).

Elimination information

87 % CO₂ formation relative to the theoretical value (8 d) (OECD Guideline 310) Readily biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

The product contains components with potential for bioaccumulation

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Sum parameter

Chemical oxygen demand (COD): 2,230 mg/g

Biochemical oxygen demand (BOD) Incubation period 5 d: 650 mg/g

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Do not allow to enter soil, waterways or waste water channels. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

13. Disposal considerations

Waste disposal of substance:

Incinerate in suitable incineration plant, observing local authority regulations. The waste codes are manufacturer's recommendations based on the designated use of the product. Other use and special waste disposal treatment on customer's location may require different waste-code assignments.

Container disposal:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 9/10
(30356025/SDS_GEN_US/EN)

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard:0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2017/10/26

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS

Safety Data Sheet

Elastocast AD52

Revision date : 2017/10/26
Version: 3.0

Page: 10/10
(30356025/SDS_GEN_US/EN)

PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET